



Main

Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Thermal-magnetic
Breaking capacity code	G

Complementary

Line Rated Current	250 A
Number of poles	3
Poles description	3P
Breaking capacity	20 KA 500 V DC 20 KA 250 V DC 65 KA 240 V AC 35 KA 480 V AC 18 kA 600 V AC
[Ue] rated operational voltage	500 V DC 600 V AC
Continuous current rating	80 %
Mounting mode	Unit mount
Electrical connection	Busbar connection line Busbar connection load
Magnetic hold current	1250 A
Magnetic tripping current	2500 A
Height	191.01 mm (7.52 in)
Width	104.65 mm (4.12 in)
Depth	127.00 mm (5 in)
Tightening torque	230.12 lbf.in (26 N.m) 0.15...0.29 in ² (95...185 mm ²) AWG 3/0...350 kcmil

Environment

Product certifications	UL listed IEC CSA CCC CE
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01115-HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901635888
Package weight(Lbs)	3.68 lb(US) (1.670 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------