

## Eaton Series G complete molded case circuit breaker

**JGH3080FAG**

**UPC:**786685928999

### **Dimensions:**

- **Height:** 7 IN
- **Length:** 3.44 IN
- **Width:** 4.13 IN

**Weight:**6 LB

### **Warranties:**

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### **Specifications:**

- **Type:** Fixed adjustable
- **Amperage Rating:** 80A
- **Interrupt Rating:** 100 kAIC at 240 Vac, 65 kAIC at 480 Vac, 25 kAIC at 600 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Fixed thermal, adjustable magnetic
- **Circuit Breaker Type:** JG
- **Circuit Breaker Frame Type:** Complete breaker
- **Frame Size:** JG-frame
- **Series:** Series G
- **Terminals:** Line and load
- **Frequency Rating:** 50/60 Hz

### **Supporting documents:**

- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [Plug-in adapters for molded case circuit](#)

breakers product aid

- High performance operating handles for Series G circuit breakers product aid
- Motor protection circuit breakers product aid
- Power metering and monitoring with Modbus RTU product aid
- Current limiting molded case circuit breaker module for series G, JG and CL
- Multi-wire lugs product aid
- Series G MCCB quick selector
- Current limiting molded case circuit breaker module product aid
- Comprehensive circuit protection for control panel applications
- Molded case circuit breakers providing higher levels of selective coordination product aid
- Circuit breaker motor operators product aid
- StrandAble terminals product aid
- Molded case circuit breakers
- Breaker service centers
- Eaton Specification Sheet - JGH3080FAG
- NG and ND-Frame molded case circuit breakers
- MOEM MCCB product selection guide

**Certifications:**

- CSA Certified
- UL Listed

**Product compliance:**

- Contact Manufacturer