



Switches > Battery Disconnect Switches



Operating Voltage: **48 VDC**  
 Switch Main Contact Current Rating: **200 A**  
 Number of Poles: **1**  
 Termination Thread Size: **M8**  
 Number of Auxiliary Contacts: **0**

## Features

### Product Type Features

Sealed Device	Yes
---------------	-----

### Configuration Features

Number of Poles	1
Number of Auxiliary Contacts	0
Switch Keying Option	Removable Without Chain

### Electrical Characteristics

Operating Voltage	48 VDC
Switch Main Contact Current Rating	200 A

### Body Features

Operating Handle Color	Green
------------------------	-------

### Mechanical Attachment

Termination Thread Size	M8
Switch Mounting Option	Round Flange
Operating Handle Type	Lever

### Dimensions

--	--

Centerline Between Flange Screw Holes	38 mm[1.5 in]
---------------------------------------	---------------

Screw Hole Diameter	7 mm[.276 in]
---------------------	---------------

### Usage Conditions

Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
-----------------------------	---------------------------

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Not Yet Reviewed
------------------------------	------------------

EU ELV Directive 2000/53/EC	Not Yet Reviewed
-----------------------------	------------------

China RoHS 2 Directive MIIT Order No 32, 2016	Not reviewed for China RoHS compliance
---	--

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Not Yet Reviewed
--	--

Halogen Content	Not Yet Reviewed for halogen content
-----------------	--------------------------------------

Solder Process Capability	Not reviewed for solder process capability
---------------------------	--


#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

### Customers Also Bought



TE Part #K1137217  
Battery Disconnecter 35-524-231-R-900



TE Part #2317659-9  
AV25 DPM 3A MOVING RING POWER  
R&G 12V FL



TE Part #EH2294-000  
DWFR-40/13-0-STK



TE Part #2-1879129-5  
RN 0402 1K47 0.1% 10PPM CUT  
LENGTH



## Documents

### Product Drawings

#### Battery Disconnecter 35-203

English

#### Battery Disconnecter 35-203

German

### CAD Files

#### 3D PDF

3D

#### Customer View Model

[ENG\\_CVM\\_CVM\\_35-203\\_1.2d\\_dxf.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_35-203\\_1.3d\\_igs.zip](#)

English

#### Customer View Model

[ENG\\_CVM\\_CVM\\_35-203\\_1.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Datasheets & Catalog Pages

#### KISSLING BATTERY DISCONNECTOR Series 35 / 200A

English