

30-511-11 ✓ ACTIVE

KISSLING | KISSLING Series 30

TE Internal #: K1132438

Power Relays, Standard, Bistable, 2 Coils, Polarized, 240 mW / 168 mW Coil Power Rating DC, .6 – .85  $\Omega$  Coil Resistance, KISSLING Series 30

[View on TE.com >](#)



Relays, Contactors & Switches > Relays > Power Relays > Power Relay, 500A, Standard, Bistable, 2 Coils, Polarized



Power Relay Type: **Standard**

Coil Magnetic System: **Bistable, 2 Coils, Polarized**

Coil Power Rating DC: **168 mW, 240 mW**

Coil Resistance: **.6 – .85  $\Omega$**

Coil Special Features: **Coil Suppression Diode**

[All Power Relay, 500A, Standard, Bistable, 2 Coils, Polarized \(6\)](#)

## Features

### Product Type Features

Power Relay Type	Standard
------------------	----------

### Electrical Characteristics

Coil Magnetic System	Bistable, 2 Coils, Polarized
Coil Power Rating DC	168 mW, 240 mW
Coil Resistance	.6 – .85 $\Omega$
Coil Special Features	Coil Suppression Diode
Coil Voltage Rating	9 VDC, 16 VDC
Contact Voltage Rating	12 VDC

### Contact Features

Contact Arrangement	1 Form X (SPST-NO-DM)
Contact Current Class	500 A
Contact Current Rating (Max)	500 A
Contact Material	AgSnO <sub>2</sub>
Contact Number of Poles	1
Relay Terminal Type	Screw Terminals

### Mechanical Attachment



Relay Mounting Type	Bracket
---------------------	---------

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Not Yet Reviewed
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Not reviewed for China RoHS compliance
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

### Compatible Parts



TE Part # CAT-AL6-KSPR30500  
Power Relay, 500A, Standard, Bistable, 2 Coils, Polarized




TE Part # K1146241  
Bi-Relais 500A 24V S-FL LK 30-511-12B

### Also in the Series | **KISSLING Series 30**



Power Relays(22)

## Customers Also Bought

TE Part #DTT-20-03  
CRIMP TOOLTE Part #K1007153  
Toggle Switch 08-1-1-13TE Part #K1060489  
Relay 29-113-12TE Part #DRC16-70SBE-P013UK  
PLG, 70P, BLK, E, SEAL BOND, BTE Part #YHDP26-24-35PEL017  
PLG, 35P, BLK, E, RNG, 16/20, PTE Part #2-2176245-2  
CRGS1206 5% 56RTE Part #K1002956  
Toggle Switch 08-4-1-13TE Part #K1008699  
Relay 26-60-05TE Part #HDP24-24-16SE-L015  
REC, 16P, BLK, E, THD, 12, STE Part #SRK-PC-080-25-601  
PIN, SOLID, SIZE M8, 25mm2, AG

## Documents

### Product Drawings

[Bi-Relay 30-511-11](#)

German

### CAD Files

[3D PDF](#)

3D

[Customer View Model](#)

[ENG\\_CVM\\_CVM\\_30-511-11\\_A.2d\\_dxf.zip](#)



English

Customer View Model

[ENG\\_CVM\\_CVM\\_30-511-11\\_A.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_30-511-11\\_A.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Datasheets & Catalog Pages

[KISSLING SINGLE POLE BI-STABLE RELAYS Series 30 / 500A](#)

English