

Distributed by:



[www.Jameco.com](http://www.Jameco.com) ♦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 154289



### 80x80x25 mm

Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H <sub>2</sub> O)	(dBA)	(g)
KD1208PTB1	13.(2)	2Ball	12	0.15	1.8	3100	41.0	0.19	35	80
KD1208PTB2	13.(2)	2Ball	12	0.12	1.4	2800	37.0	0.16	32	80
KD1208PTB3	13.(2)	2Ball	12	0.09	1.1	2500	33.1	0.13	28	80
KD1208PTS1	13	Sleeve	12	0.16	1.9	3000	40.0	0.18	33	80
KD1208PTS2	13	Sleeve	12	0.13	1.6	2700	36.5	0.15	31	80
KD1208PTS3	13	Sleeve	12	0.10	1.2	2300	31.0	0.11	26	80
KD2408PTB1	13.(2).A	2Ball	24	0.07	1.7	3100	41.0	0.19	35	80
KD2408PTB2	13.(2).A	2Ball	24	0.06	1.4	2800	37.0	0.16	32	80
KD2408PTB3	13.(2).A	2Ball	24	0.05	1.2	2500	33.1	0.13	28	80
KD2408PTS1	13.A	Sleeve	24	0.08	1.9	3000	40.0	0.18	33	80
KD2408PTS2	13.A	Sleeve	24	0.06	1.4	2700	36.5	0.15	31	80
KD2408PTS3	13.A	Sleeve	24	0.05	1.2	2300	31.0	0.11	26	80

### 92x92x25 mm

Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H <sub>2</sub> O)	(dBA)	(g)
KD1209PTB1	13.(2)	2Ball	12	0.16	1.9	2800	49.0	0.17	35	95
KD1209PTB2	13.(2)	2Ball	12	0.14	1.7	2600	48.0	0.15	33	95
KD1209PTB3	13.(2)	2Ball	12	0.10	1.2	2300	41.0	0.11	30	95
KD1209PTS1	13	Sleeve	12	0.17	2.0	2800	49.0	0.16	34	95
KD1209PTS2	13	Sleeve	12	0.14	1.7	2500	44.5	0.14	32	95
KD1209PTS3	13	Sleeve	12	0.11	1.3	2200	39.0	0.11	28	95
KD2409PTB1	13.(2).A	2Ball	24	0.09	2.2	2800	49.0	0.17	35	95
KD2409PTB2	13.(2).A	2Ball	24	0.06	1.4	2600	48.0	0.15	33	95
KD2409PTB3	13.(2).A	2Ball	24	0.05	1.2	2300	41.0	0.11	30	95
KD2409PTS1	13.A	Sleeve	24	0.09	2.2	2800	49.0	0.16	34	95
KD2409PTS2	13.A	Sleeve	24	0.07	1.7	2500	44.5	0.14	32	95
KD2409PTS3	13.A	Sleeve	24	0.05	1.2	2200	39.0	0.11	28	95

\*Specifications subject to change without notice.