

Eaton Series C complete molded case circuit breaker

KD3225M01Z01

UPC:782116048625

Dimensions:

- **Height:** 5.5 IN
- **Length:** 4.1 IN
- **Width:** 5.5 IN

Weight:11.5 LB

Notes:TA300K terminals

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Amperage Rating:** 225A
- **Interrupt Rating:** 65 kAIC at 240 Vac, 35 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** KD
- **Circuit Breaker Frame Type:** Complete breaker
- **Frame Size:** K-frame
- **Series:** Series C
- **Terminals:** Optional line and load
- **Frequency Rating:** 50-60 Hz
- **Mounting Hardware:** Single-pole imperial mounting base

Supporting documents:

- [UL listed 100%-rated molded case circuit breakers](#)

- Application of Tap Rules to Molded Case Breaker Terminals
- Application of Multi-Wire Terminals for Molded Case Circuit Breakers
- Circuit breaker motor operators product aid
- Current limiting Series C molded case circuit breakers product aid
- Multi-wire lugs product aid
- StrandAble terminals product aid
- Power metering and monitoring with Modbus RTU product aid
- Motor protection circuit breakers product aid
- Plug-in adapters for molded case circuit breakers product aid
- Eatons Volume 4-Circuit Protection
- Molded case circuit breakers
- Instruction Leaflet for the KES 310+ Electronic Trip Unit
- Installation Instructions for DK, KDB, KD, HKD, KDC, KW, HKW, KWC, CKD, CHKD Circuit Breakers and Molded Case Switches
- Breaker service centers
- Series C J-Frame molded case circuit breakers time current curves
- Series C F-Frame molded case circuit breakers
- Eaton Specification Sheet - KD3225M01Z01
- MOEM MCCB product selection guide
- Series C G-Frame molded case circuit breakers time current curves

Certifications:

- UL Listed

Product compliance: No Data