




NOTES:

1. FOR USE WITH RG-9, 9A, 9B AND 214/U CABLE.
2. FOR CABLING INSTRUCTIONS SEE CP 211A.
3. FOR CABLE TRIMMING USE KTJ-33 & KTJ-81
4. FOR CRIMPING USE DIE SIZE 04.

STAMP: KINGS KN-59-53.

S-D

KN-59-53

REVISIONS	
ISSUE	CHANGES
1	CN 2862 C 11 JAN 65
2	CN 3857 A 22 APR 68 H.R.
3	CN 6003 A J.M. 27 MAY 68
4	CN 7780 A R.H.W. 30 JUL 69
5	CN 7840 A R.H.W. 8 AUG 69
6	CN 8579 A L.R. 22 MAY 70
7	CN 16745 E GA 1 FEB 77
8	CN 27408 D SD 26 SEP 85

S-D

S-D

17	1	K-GRIP SLEEVE	S-89-24-2-MC7
16	1	CONTACT	
15	1	COUPLING NUT	
14	1	GASKET	
13	1	SPRING	
11	1	INSULATOR	
10	1	CONTACT	
8	1	CONTACT	D-59-14-1-M07
7	1	INSULATOR	
6	1	WASHER	571-5-MC7
5	1	K-GRIP	S-89-35-1-MC7
4	1	GASKET	571-3-M99
3	1	GLAND	S-89-35-9-MC7
2	1	BODY ASSY	
1	1	CLAMP NUT	S-89-35-5-MC7
ITEM	REQD.	DESCRIPTION	DRAWING NO.

UNLESS OTHERWISE SPECIFIED:

1. TOLERANCES:
FRACTIONS & .010 DECIMAL ±.004 ANGLES ± 0° 30'
T. I. R. CONCENTRICITY OF A / 2 DIAMETERS MAY NOT EXCEED THE SUM OF THEIR TOLERANCES.
2. REMOVE ALL BURRS. BREAK SHARP EDGES .003 MAX.
3. NO FILLETS PERMITTED.
4. SURFACE ROUGHNESS 100 MICROINCHES RMS MAX.
5. ALL DIMENSIONS PRIOR TO PLATING.

REF.

FINISH

SPEC.

MATL.

SPEC.

N ANGLE PLUG

DRAWN L1 DATE 31 JUL 62

APPR. DATE

KINGS ELECTRONICS
40 MARBLEDALE ROAD
TUCKAHOE, N. Y.

KN-59-53