

# LA9LB920

Current limiter, TeSys U / TeSys GV2,  
32A/690V, activation 1kA, Iq 100kA@440V,  
DIN rail mounting



## Main

Range	TeSys
Range of product	TeSys U TeSys GV2
Accessory / separate part category	Protection accessory
Product or component type	Current limiting module
Range compatibility	TeSys (TeSys U) TeSys (TeSys GV2)
Product compatibility	LUB LU2B GV2P GV2L GV2RT GV2ME
Function of module	Increasing the breaking capacity of a circuit breaker
Mounting location	35 mm DIN rail
[Ie] rated operational current	32 A
[Ith] conventional free air thermal current	63 A conforming to IEC 60947-1
Activation threshold	1000 A
Breaking capacity	<= 100 kA depending on protective device
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to IEC 60947-1

## Complementary

Connections - terminals	Screw clamp terminals 1 x 1.5...25 mm <sup>2</sup> rigid Screw clamp terminals 2 x 1.5...10 mm <sup>2</sup> rigid Screw clamp terminals 1 x 1.5...25 mm <sup>2</sup> flexible without cable end Screw clamp terminals 2 x 1.5...10 mm <sup>2</sup> flexible without cable end Screw clamp terminals 1 x 1.5...16 mm <sup>2</sup> flexible with cable end Screw clamp terminals 2 x 1.5...4 mm <sup>2</sup> flexible with cable end
Tightening torque	2.2 N.m
Net weight	0.32 kg

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	8.5 cm
Package 1 Length	15.7 cm
Package 1 Weight	346.9 g
Unit Type of Package 2	S02
Number of Units in Package 2	12
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 2 Length	40.0 cm
Package 2 Weight	4.494 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 Monate
----------	-----------