



### Main

Device short name	IFM
Product or component type	Interface module
Range compatibility	Masterpact (MasterPact MTZ) Masterpact (MasterPact NT) Masterpact (MasterPact NW) ComPact (ComPact NSX) ComPact (ComPact NS630b...1600) ComPact (ComPact NS1600b...3200) PowerPact (PowerPact J) PowerPact (PowerPact L) PowerPact (PowerPact H) PowerPact (PowerPact P) PowerPact (PowerPact R)

### Complementary

Communication network type	Universal Logic Plug on 2-port RJ45 Modbus, Modbus Serial line slave 9.6...38.4 kbauds on 1 RJ45
Mounting mode	By clips
Mounting support	35 mm DIN rail
Accuracy class	Class 2 power supply
Input voltage	24 V DC - 20...10 %
Output voltage	24 V DC
Output current	3 A
Current consumption	30 mA 24 V DC room temperature
Power consumption in W	1.635 W
Memory type	EEPROM data storage
Connections - terminals	RJ45 connector Screw type terminals
Product certifications	EAC CULus CE FCC
Standards	CISPR 22 UL 61010 UL 60950 CISPR 24 CISPR 11 IEC 60950 IACS E10
Height	109 mm
Width	18 mm
Depth	73 mm
Net weight	120 g

### Environment

IP degree of protection	Connectors: IP20 Other parts: IP30
Relative humidity	5...85 % at 55 °C without condensation
Ambient air temperature for storage	-40...85 °C
Ambient air temperature for operation	-20...70 °C
Pollution degree	3
Flame retardance	V0 conforming to UL 94

Shock resistance	+/- 15 gn 11 ms conforming to EN/IEC 60068-2-27
Vibration frequency	5...8.4 Hz conforming to EN/IEC 60068-2

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.323 cm
Package 1 Width	7.949 cm
Package 1 Length	11.525 cm
Package 1 Weight	120.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	54
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	7.211 kg
Unit Type of Package 3	P06
Number of Units in Package 3	432
Package 3 Height	75 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	67 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------