



Main

Range of product	PacDrive 3
Product or component type	Single drive
Device short name	LXM 62

Complementary

Product compatibility	Servo motor SH3 (140 mm, 4 motor stacks) optimized in terms of torque and speed Servo motor SH3 (205 mm, 1 motor stacks) optimized in terms of torque and speed Servo motor MH3 (140 mm, 2 motor stacks) optimized in terms of torque and speed Servo motor MH3 (140 mm, 3 motor stacks) optimized in terms of torque and speed Servo motor MH3 (190 mm, 1 motor stacks) optimized in terms of torque and speed Servo motor SHS Servo motor SH3 (140 mm, 2 motor stacks) optimized in terms of torque and speed Servo motor SH3 (140 mm, 3 motor stacks) optimized in terms of torque and speed Servo motor MH3 (100 mm, 3 motor stacks) optimized in terms of torque and speed Servo motor MH3 (140 mm, 1 motor stacks) optimized in terms of torque and speed
Network number of phases	Single phase Three phase
[Us] rated supply voltage (through power supply module)	400 V three phase (tolerance: - 10...10 %) 230 V three phase (tolerance: - 10...10 %) 230 V single phase (tolerance: - 10...10 %)
Supply frequency	50/60 Hz +/-5 %
Continuous output current	20 A at 4 kHz
Output current 3s peak	45 A at 4 kHz
Continuous power	9.6 kW
Nominal power	9.6 kW
Overvoltage category	III
Electrical connection	Terminal, clamping capacity: 0.2...15 mm ² , AWG 24...AWG 16 (CN4) Terminal, clamping capacity: 0.5...16 mm ² , AWG 20...AWG 6 (CN5) Terminal, clamping capacity: 0.75...16 mm ² , AWG 18...AWG 6 (CN6) Terminal, clamping capacity: 0.2...6 mm ² , AWG 24...AWG 10 (CN7)
Tightening torque	CN1: 2.5 N.m
Number of inputs	2 digital 2 touch probe
Discrete input voltage	24 V DC for - 20...25 %
Number of outputs	2 digital
Discrete output voltage	24 V DC
Safety function	STO (safe torque off)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Physical interface	SERCOS III
Net weight	3 kg

Environment

Standards	EN 61800-5-2 EN/ISO 13849-1 EN 61800-3 CSA C22.2 No 14 EN 62061 UL 508C IEC 62061 EN/ISO 13849-2 IEC 61508 EN 61800-5-1
Product certifications	CE EAC UL CSA TÜV
IP degree of protection	IP20 conforming to EN/IEC 60529
Vibration resistance	10 m/s ² conforming to EN/IEC 60721-3-3
Shock resistance	100 m/s ² conforming to EN/IEC 60721-3-3
Pollution degree	2 conforming to EN/IEC 61800-5-2
Environmental characteristic	3K3 conforming to IEC 60721-3-3
Relative humidity	5...85 %
Ambient air temperature for operation	5...55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.2 cm
Package 1 Width	30.0 cm
Package 1 Length	42.5 cm
Package 1 Weight	3.91 kg
Unit Type of Package 2	S06
Number of Units in Package 2	10
Package 2 Height	75.0 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	52.1 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 Monate
----------	-----------