

Customer Information Sheet

DRAWING No.: M20-106XX00


IF IN DOUBT - ASK

©

NOT TO SCALE

THIRD ANGLE PROJECTION



ALL DIMENSIONS IN mm



ORDER CODE:

M20-106XX00

No. OF CONTACTS:
 01 TO 12



SECTION X-X

SPECIFICATIONS:

ELECTRICAL:

CURRENT RATING = 3A AC/DC

VOLTAGE RATING = 250V AC MAX

CONTACT RESISTANCE = 20mΩ MAX

INSULATION RESISTANCE = 5,000MΩ MIN

DIELECTRIC STRENGTH = 1,500V AC FOR 1 MINUTE

ENVIRONMENTAL:

TEMPERATURE RANGE = -40°C TO +105°C

NOTES:

1. CONTACT No. 1 IDENTIFICATION.
2. FOR USE WITH CRIMP CONTACTS:
M20-11600XX (RELDED CONTACTS),
M20-11800XX (LOOSE CONTACTS).
3. THE ABOVE SPECIFICATIONS APPLY
WHEN THIS MOULDING IS USED
WITH THE SPECIFIED CONTACTS.
4. FOR COMPLETE ELECTRICAL AND
MECHANICAL SPECIFICATION, SEE
COMPONENT SPECIFICATION C001XX
(LATEST ISSUE).

SB	6	14.07.14	12528
NAME	ISS.	DATE	C/NOTE
APPROVED:		S.BENNETT	
CHECKED:		M.PLESTED	
DRAWN:		S.BENNETT	
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.

TOLERANCES

X. = ±1mm
X.X = ±0.50mm
X.XX = ±0.10mm
X.XXX = ±0.01mm

ANGLES = ±5°

UNLESS STATED

MATERIAL:

PPE+PS
UL94V-1 BLACK

FINISH: CLEAN, FLASH-FREE

S/AREA: mm²

TITLE:

2.54mm PITCH SIL
CRIMP MOULDING

DRAWING NUMBER:

M20-106XX00

SHT
2 OF 2