

Customer Information Sheet

DRAWING No.: M30-600XX46

SHEET 2 OF 2

IF IN DOUBT - ASK

(C)

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm

SPECIFICATIONS:

MATERIAL:

MOULDING - POLYAMIDE 46 NATURAL, UL94V-0

CONTACT - BRASS

RETAINER - PHOSPHOR BRONZE

FINISH:

CONTACT & RETAINER - 100% TIN

ELECTRICAL:

RATED CURRENT - 1A AC/DC

RATED VOLTAGE - 150V AC/DC

DIELECTRIC STRENGTH - 500V AC

INSULATION RESISTANCE - 1000 MEGOHMS MIN

DIELECTRIC WITHSTANDING VOLTAGE - 500V AC

ENVIRONMENTAL:


TEMPERATURE RANGE - -55°C TO +85°C

PACKING: TUBE

FOR COMPLETE SPECIFICATIONS,
SEE COMPONENT SPECIFICATION
C025XX (LATEST ISSUE)

$1.25 \times \text{No. OF WAYS} + 1.85 \pm 0.10$

$1.25 \times \text{No. OF WAYS} + 0.85 \pm 0.05$



RECOMMENDED
PAD LAYOUT

NOTES:


1. ALL TOLERANCES ARE ± 0.30 UNLESS OTHERWISE STATED.
2. MATES WITH M30-1000046 CRIMP CONTACTS AND M30-110XX00 CRIMP MOULDING.
3. COPLANARITY OF CONTACTS AND RETAINER. TO BE 0.1mm MAX.

ORDER CODE:




M30-600XX46

No. OF WAYS _____
02 TO 15

FINISH: _____
46 = 100% TIN



SECTION A-A



RA	8	20.01.09	10265
NAME	ISS.	DATE	C/NOTE
APPROVED:			
CHECKED:			
DRAWN:	W. J. BOURNE		
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.

TOLERANCES
X. = $\pm 1\text{mm}$
X.X = $\pm 0.25\text{mm}$
X.XX = $\pm 0.10\text{mm}$
X.XXX = $\pm 0.01\text{mm}$
ANGLES = $\pm 5^\circ$
UNLESS STATED

MATERIAL:

SEE ABOVE

FINISH: SEE ABOVE

S/AREA: mm²

TITLE:

1.25mm PITCH SIL
SMT BOARD MOUNT CONNECTOR

DRAWING NUMBER:

M30-600XX46

SHT
2
OF
2