



MODIFICATION DESCRIPTION

SHEET 1 OF 1

-529

MOD

THIS MODIFICATION APPLIES TO THE FOLLOWING LINES AND SIZES ONLY

LINE	DS	DA												
CONN. SIZE	3/61	3/61												

RELEASED TO SALES
THE DEUTSCH COMPANY

77-862 NOP

- 529** SPECIAL COMBINATION - INSERT DESIGN (WIRE SEAL) SPECIAL ITEMS (SAFETY WIRE) FINISH (ANODIZE PLATING) CONTACTS (PLATING)
Applies to all connectors listed above.
To be supplied with MODS:
 - 067 (rear inserts with smaller than std. wire seals)
 - 430 (coupling ring to have safety wire holes)
 - 006 (contacts to be plated .000100 gold over copper)
 all aluminum parts to be anodized per mod
 -538 (alumilite 203 clear finish .00035 thick)
 except plug shell anodized per mod
 -045 (alumilite 225 hard anodize clear finish .0004 thick)
 ferrous metal parts to be plated per mod
 -536 (tin plate .0004-.0005 thick)
 except balls and coil springs to be unplated and wafer springs to be plated per mod
 -537 (gold plated .000005-.000015)

SPECIAL APPLICATION

On die cast parts, finish will not be clear.

RELEASE DATE 6-26-68
 SUPERCEDES 1-1-63
 APPROVED *mk*
Rou n. H
 PROJ. ENG. TEC. DEV. C. OF ENGS.