



### Main

Range	Multi9
Product or component type	Comb busbar
Mounting mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	1L
Length in 18 mm modules	57

### Complementary

Number of ways	57 ways 1 L
Poles configuration for 1 way	1 x 1P
Connection pitch	18 mm
Connector type	Tooth
Distance between way	18 mm
Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	80 A at 40 °C
[Ue] rated operational voltage	480 V AC 50/60 Hz Ph/Ph 277 V AC 50/60 Hz Ph/N
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to UL 508
Mounting location	Top on tunnel type terminals
9 mm pitches	114
Width	1026 mm
Colour	Light grey (RAL 7035)
Range compatibility	Multi 9 (Multi9 C60BP)

### Environment

Standards	UL 508
Fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1
Pollution degree	3
IP degree of protection	IP20 with end-pieces and tooth covers

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.100 cm
Package 1 Width	6.100 cm
Package 1 Length	102.500 cm
Package 1 Weight	820.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	9.700 cm
Package 2 Width	11.500 cm

Package 2 Length	108.000 cm
Package 2 Weight	4.387 kg
Unit Type of Package 3	P12
Number of Units in Package 3	35
Package 3 Height	112.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	42.709 kg

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 Monate
----------	-----------