



#### MAS/MAK-series



#### **Product description**

Shielded miniature multipole connectors, 3- pole to 8-pole.

- Numerous different versions ensure a variety of uses in audio- and video equipment, measurement and control instruments, on projectors and in the computer technology
- Safe connection of connector, couplings, panel-mounted sockets and panel-mounted connectors with screw locking system
- All cable connectors feature clamping tabs to relieve the strain
- UM types as standard, but industry package, quantity boxed: 1000 units

#### Basic data

Operating voltage: 34 V AC / DC Operating current: 4 A Flashover voltage: 1 kV Insulation resistance:  $10^{11}\,\Omega$  Type of connection: solder Plug illustrations: EN 60130-9

| Туре                    |   | Number of poles | Description  | Colour                               | Order no.  |
|-------------------------|---|-----------------|--|--------------------------------------|--|
| MAS 30<br>MAS 30 UM     | - 7                                     | 3               | Connector with insulated handle, solder connection | grey<br>UM black<br>UM grey          | 930 014-517<br>931 002-100<br>931 002-117                |
| MAS 40<br>MAS 40 UM     | - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 | 4 4 1           | Connector with insulated handle, solder connection | grey<br>UM grey                      | 930 015-517<br>931 018-117                               |
| MAS 50<br>MAS 50 UM     | - 7 7                                   | 5               | Connector with insulated handle, solder connection | grey<br>UM black<br>UM grey          | 930 016-517<br>931 034-100<br>931 034-117                |
| MAS 50 S<br>MAS 50 S UM | 8<br>8<br>9<br>10<br>13.2               | 5               | Connector with insulated handle, solder connection | black<br>grey<br>UM black<br>UM grey | 930 131-500<br>930 131-517<br>931 036-100<br>931 036-117 |











| Туре                      |   | Number of poles                 | Description  | Colour                               | Order no.  |
|---------------------------|---|---------------------------------|--|--------------------------------------|--|
| MAS 50 W                  | 9 LE 0 13.2   | 5                               | Connector with insulated handle, solder connection | grey                                 | 930 805-517  |
| MAS 60<br>MAS 60 UM       | - 7   | 6                               | Connector with insulated handle, solder connection | black<br>grey<br>UM black<br>UM grey | 930 017-500<br>930 017-517<br>931 044-100<br>931 044-117 |
| MAS 70 S<br>MAS 70 S UM   | 7 7 7 7 7   | 7<br>3<br>3<br>7<br>4<br>1<br>1 | Connector with insulated handle, solder connection | black<br>grey<br>UM black<br>UM grey | 930 356-500<br>930 356-517<br>931 050-100<br>931 050-117 |
| MAS 80 S<br>MAS 80 S UM   | 9 1 1 2 1 3 | 8                               | Connector with insulated handle, solder connection | black<br>grey<br>UM black<br>UM grey | 930 298-500<br>930 298-517<br>931 183-100<br>931 183-117 |
| MAS 80 SN<br>MAS 80 SN UM | 9 1 1 2 1 3 | 8                               | Connector with insulated handle, solder connection | black<br>grey<br>black UM<br>grey UM | 931 518-500<br>931 518-517<br>931 521-100<br>931 521-117 |









| Туре                        |   | Number of poles | Description   | Colour                      | Order no.                                 |
|-----------------------------|---|-----------------|---|-----------------------------|---|
| MAWI 30 B<br>MAWI 30 B UM   | 1.5<br>31<br>= 52.5<br>Fur Kabel<br>0 6.5       | 3               | Angled connector with insulated handle, solder connection | grey<br>UM black<br>UM grey | 931 597-517<br>931 621-100<br>931 621-117 |
| MAWI 40 B                   | 1,5<br>2,1<br>31<br>-52,5<br>Fur Kabel<br>0 6,5 | 4 4 2 1         | Angled connector with insulated handle, solder connection | grey                        | 931 567-517                               |
| MAWI 50 B                   | 1,5<br>31<br>= 52.5<br>For Kabel<br>0 6,5       | 5               | Angled connector with insulated handle, solder connection | grey                        | 931 569-517                               |
| MAWI 50 SB<br>MAWI 50 SB UM | 1.5<br>2.5<br>31<br>-52.5<br>Fur Kabel<br>6.5   | 5               | Angled connector with insulated handle, solder connection | grey<br>UM black<br>UM grey | 931 571-517<br>931 572-100<br>931 572-117 |
| MAWI 60 B<br>MAWI 60 B UM   | 1.5<br>31<br>= 52.5<br>Für Kabol 6.5            | 6               | Angled connector with insulated handle, solder connection | grey<br>UM black<br>UM grey | 931 573-517<br>931 574-100<br>931 574-117 |









| Туре                            |  | Number of poles            | Description  | Colour                       | Order no.                                 |
|---------------------------------|--|----------------------------|--|------------------------------|---|
| MAWI 70 SB                      | 1.5<br>2.5<br>31<br>- 52.5<br>Fur Kabel<br>6.5<br>6.5  | 7                          | Angled connector with insulated handle, solder connection  | grey                         | 931 575-517                               |
| MAWI 80 SB<br>MAWI 80 SB UM     | 1.5<br>31<br>= 52.5<br>Für Kabel<br>6.5<br>0 13.2  | 8<br>5<br>3<br>8<br>1<br>7 | Angled connector with insulated handle, solder connection  | grey<br>UM black<br>UM black | 931 740-517<br>931 741-100<br>931 741-117 |
| MAWI 80 SN B<br>MAWI 80 SN B UM | 1.5<br>V L 0<br>31<br>= 52.5<br>Fur Kabel<br>0 6.5<br>0 13.2                                       | 8                          | Angled connector with insulated handle, solder connection  | grey<br>UM black<br>UM grey  | 931 577-517<br>931 578-100<br>931 578-117 |
| MASEI 3                         | 28.5<br>22.2<br>22.2<br>27<br>27<br>27<br>27<br>27<br>27<br>27<br>27<br>27<br>27<br>27<br>27<br>27 | 3                          | Panel-mounted connector with flange, solder connection, die-cast casing and and flange,nickel-plated |                              | 930 063-500                               |
| MASEI 5 S                       | 28.5<br>22.2<br>015.2<br>915.2<br>913.6  | 5                          | Panel-mounted connector with flange, solder connection, die-cast casing and and flange,nickel-plated |                              | 930 934-500                               |









| Туре                    |                                    | Number of poles | Description                                       | Colour                      | Order no.                                 |
|-------------------------|------------------------------------|-----------------|---|-----------------------------|---|
| MAK 30 S<br>MAK 30 S UM | 92.5                               | 3<br>1 (2)3     | Coupling with insulated handle, solder connection | grey<br>UM grey             | 930 149-517<br>931 080-117                |
| MAK 40<br>MAK 40 UM     | 97.5                               | 2 3 1 1 1 4     | Coupling with insulated handle, solder connection | grey<br>UM black<br>UM grey | 930 150-517<br>931 086-100<br>931 086-117 |
| MAK 50                  | 97.5<br>9<br>9<br>9<br>9<br>9<br>9 | 5               | Coupling with insulated handle, solder connection | grey                        | 930 151-517                               |
| MAK 50 S<br>MAK 50 S UM | 37.5<br>9                          | 5               | Coupling with insulated handle, solder connection | grey<br>UM black<br>UM grey | 930 172-517<br>931 092-100<br>931 092-100 |
| MAK 60<br>MAK 60 UM     | 97.5                               | 6 3 4 1 5 5     | Coupling with insulated handle, solder connection | grey<br>UM black            | 930 152-517<br>931 100-100                |









| Туре      |   | Number of poles       | Description                                       | Colour | Order no.   |
|-----------|---|-----------------------|---|--------|-------------|
| MAK 70 S  | 937.5   | 7<br>1<br>1<br>6<br>7 | Coupling with insulated handle, solder connection | grey   | 930 388-517 |
| MAK 80 S  | 97.5<br>90<br>171<br>171<br>171<br>171<br>171<br>171<br>171<br>17 | 8                     | Coupling with insulated handle, solder connection | grey   | 930 348-517 |
| MAK 80 SN | 937.5   | 8                     | Coupling with insulated handle, solder connection | grey   | 931 519-517 |
| MAB 3 S   | 28.5<br>22.2<br>7<br>8<br>1<br>1,21<br>1,21<br>9,61               | 3<br>1 2 3            | Panel-mounted socket with flange                  | black  | 930 018-200 |
| MAB 4     | 28.5<br>22.2<br>7<br>0 14.9<br>0 12.0<br>0 12.0                   | 2 3 1 1 4             | Panel-mounted socket with flange                  | black  | 930 009-200 |









| Туре    |   | Number of poles                 | Description                      | Colour | Order no.   |
|---------|---|---------------------------------|----------------------------------|--------|-------------|
| MAB 5   | 28.5<br>22.2<br>22.2<br>3 14.9<br>9 17.2                  | 5<br>2<br>1<br>1<br>1<br>5      | Panel-mounted socket with flange | black  | 930 010-200 |
| MAB 5 S | 28.5<br>22.2<br>22.2<br>7<br>8.0<br>1.3,9<br>9.81         | 5<br>1<br>2<br>5<br>3           | Panel-mounted socket with flange | black  | 930 071-200 |
| MAB 6   | 28.5<br>22.2<br>22.2<br>7<br>6.0<br>1.3.9<br>9.0<br>1.7.1 | 6                               | Panel-mounted socket with flange | black  | 930 011-200 |
| MAB 7 S | 28.5<br>22.2<br>22.2<br>2 E E T 1.2<br>2 14.9<br>9 E 1.2  | 7<br>4<br>2<br>5<br>1<br>6<br>7 | Panel-mounted socket with flange | black  | 930 343-200 |
| MAB 8 S | 28.5<br>22.2<br>7<br>7<br>8 67<br>7 7                     | 8<br>4<br>1<br>7<br>7<br>8      | Panel-mounted socket with flange | black  | 930 345-200 |









| Туре       |   | Number of poles   | Description   | Colour | Order no.   |
|------------|---|---|---|--------|-------------|
| MAB 8 SN   | 28.5<br>22.2<br>22.2<br>22.2<br>2.5<br>2.5<br>2.5<br>2.5<br>2.5<br>2. | 8<br><sup>8</sup> <sup>2</sup> <sup>5</sup> <sup>1</sup> <sup>6</sup> <sup>7</sup> <sup>7</sup> | Panel-mounted socket with flange  | black  | 931 613-200 |
| MAB 5 SV   | 7 7 9 12  | 5   | Panel-mounted socket for printed circuits, Plug-in direction perpendicular to the circuit board | black  | 930 777-200 |
| MAB 6 V    | 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2                                 | 6   | Panel-mounted socket for printed circuits, Plug-in direction perpendicular to the circuit board | black  | 930 812-200 |
| MAB 7 SV   | 9 12 0 12 0 12 0 12 0 12 0 12 0 12 0 12                               | 7<br>1<br>1<br>6<br>1<br>7  | Panel-mounted socket for printed circuits, Plug-in direction perpendicular to the circuit board | black  | 931 657-200 |
| MAB 8 SN V | 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2                                 | 8<br>4<br>1<br>1<br>7<br>1<br>8   | Panel-mounted socket for printed circuits, Plug-in direction perpendicular to the circuit board | black  | 932 664-200 |









| Туре     |   | Number of poles   | Description  | Colour | Order no.   |
|----------|---|---|--|--------|-------------|
| MAB 8 SV | 9 12 0 12 0 12 0 12 0 12 0 12 0 12 0 12 | 8<br><sup>8</sup> <sup>2</sup> <sup>5</sup> <sup>3</sup> <sup>7</sup> | Panel-mounted socket for printed circuits, Plug-in direction perpendicular to the circuit board                                | black  | 931 735-200 |
| MAB 3 SH | 3.5 10 2.2 2.1 Expenses 0.5 mm tiefer   | 3<br>1 2 3  | Panel-mounted socket<br>for printed circuits,<br>Plug-in direction parallel<br>to the circuit board,<br>Board thickness 1,5 mm | black  | 930 360-200 |
| MAB 5 SH | 3.5. 10. 4.2 Ensatz O.5 mm lider        | 5   | Panel-mounted socket<br>for printed circuits,<br>Plug-in direction parallel<br>to the circuit board,<br>Board thickness 1,5 mm | black  | 931 744-200 |
| MAB 5 WH |   | 5   | Panel-mounted socket<br>for printed circuits,<br>Plug-in direction parallel<br>to the circuit board,<br>Board thickness 1,5 mm | black  | 930 236-200 |
| MAB 6 H  | 35 10 42 35                             | 6 3 2 4 1 5 5   | Panel-mounted socket<br>for printed circuits,<br>Plug-in direction parallel<br>to the circuit board,<br>Board thickness 1,5 mm | black  | 930 778-200 |









| Туре                    |  | Number of poles                 | Description  | Colour          | Order no.                  |
|-------------------------|--|---------------------------------|--|-----------------|----------------------------|
| MAB 7 SH-L              | 3.5 10 4.2   | 7<br>1<br>1<br>6<br>1<br>1<br>7 | Panel-mounted socket<br>for printed circuits,<br>Plug-in direction parallel<br>to the circuit board,<br>Board thickness 1,5 mm | black           | 930 518-200                |
| MAB 8 SH                | 3.5 10 42 21 22 21 25 21 | 8<br>6 2 5<br>1 5 3<br>7        | Panel-mounted socket<br>for printed circuits,<br>Plug-in direction parallel<br>to the circuit board,<br>Board thickness 1,5 mm | black           | 931 399-200                |
| MABU LD-V               | 52 min.  | -                               | Connecting socket for<br>58 mm panel-mounted<br>sockets, can be equiped<br>with flanged panel-mounted<br>sockets, e.g. MAB 5S  | ivory           | 930 698-108                |
| AR 20                   |  | -                               | Surface-mounted frame for MABU LD-V  | ivory           | 933 650-001                |
| MAS 3100<br>MAS 3100 UM | 9 9 9 M16 x 0.75   | 3 ( • • • )1                    | Connector with locking screw, solder connection  | grey<br>UM grey | 930 304-517<br>931 068-117 |









| Туре                        |               | Number of poles       | Description                                     | Colour                      | Order no.                                 |
|-----------------------------|---------------|-----------------------|---|-----------------------------|---|
| MAS 4100<br>MAS 4100 UM     | 27 M16 x 0.75 | 4                     | Connector with locking screw, solder connection | grey<br>UM black<br>UM grey | 930 963-517<br>931 173-100<br>931 173-117 |
| MAS 5100<br>MAS 5100 UM     | 27 M16 x 0.75 | 5                     | Connector with locking screw, solder connection | grey<br>UM black<br>UM grey | 930 964-517<br>931 189-100<br>931 189-117 |
| MAS 5100 S<br>MAS 5100 S UM | 27 M16 x 0.75 | 5                     | Connector with locking screw, solder connection | grey<br>UM grey             | 930 965-517<br>931 174-117                |
| MAS 6100<br>MAS 6100 UM     | 97 M16 x 0.75 | 6 3 2 5 1             | Connector with locking screw, solder connection | grey<br>UM grey             | 930 966-517<br>931 151-117                |
| MAS 7100 S<br>MAS 7100 S UM | 27 M16 x 0.75 | 7<br>3<br>3<br>1<br>1 | Connector with locking screw, solder connection | grey<br>UM grey             | 930 688-517<br>930 689-117                |











| Туре           |   | Number of poles | Description  | Colour                      | Order no.                                 |
|----------------|---|-----------------|--|-----------------------------|---|
| MAS 8100 S     | 97 M16 x 0.76   | 8 3 4 3 4 7     | Connector with locking screw, solder connection        | grey<br>UM black<br>UM grey | 930 539-517<br>931 240-100<br>931 240-117 |
| MAS 8100 SN UM | 27 - 41 - M16 x 0.75  | 8               | Connector with locking screw, solder connection        | UM black<br>UM grey         | 931 750-100<br>931 750-117                |
| MAWI 3100      | 90 P P P P P P P P P P P P P P P P P P P                                    | 3               | Angled connector with locking screw, solder connection | grey                        | 932 906-117                               |
| MAWI 4100      | -52.6<br>-31<br>-31<br>-31<br>-31<br>-31<br>-31<br>-31<br>-31<br>-31<br>-31 | 4               | Angled connector with locking screw, solder connection | grey                        | 932 907-117                               |
| MAWI 5100      | #52.5 O O O O O O O O O O O O O O O O O O O                                 | 5  4  3  5  1   | Angled connector with locking screw, solder connection | grey                        | 932 908-117                               |









| Туре        |  | Number of poles | Description   | Colour | Order no.   |
|-------------|--|-----------------|---|--------|-------------|
| MAWI 5100 S | ## ## ## ## ## ## ## ## ## ## ## ## ##   | 5               | Angled connector with locking screw, solder connection        | grey   | 932 909-117 |
| MAWI 6100   | 20 Y Short S | 6 3 2 5 1       | Angled connector with locking screw, solder connection        | grey   | 932 910-117 |
| MAWI 8100 S | 20 span  | 8               | Angled connector with locking screw, solder connection        | grey   | 932 912-117 |
| MASEI 3100  | 7<br>M18x0,75<br>W1 0 13,2<br>M16 x 0,75   | 3               | Panel-mounted connector with locking screw, solder connection | grey   | 930 296-517 |
| MASEI 4100  | M18x0.75   | 4 4 4 1         | Panel-mounted connector with locking screw, solder connection | grey   | 930 955-517 |









| Туре                        |  | Number of poles | Description   | Colour                      | Order no.                                 |
|-----------------------------|--|-----------------|---|-----------------------------|---|
| MASEI 5100                  | 7<br>7<br>M18x0.75<br>0 3.2<br>M16 x 0.75  | 5               | Panel-mounted connector with locking screw, solder connection | grey                        | 930 956-517                               |
| MASEI 5100 S                | 7<br>7<br>M18x0,75<br>Q2<br>Q3,2<br>M16 x 0,75   | 5 3 4 1         | Panel-mounted connector with locking screw, solder connection | grey                        | 930 957-517                               |
| MASEI 6100                  | 7<br>7<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0 | 6 3 4 2 5 1     | Panel-mounted connector with locking screw, solder connection | grey                        | 930 958-517                               |
| MAK 3100 S<br>MAK 3100 S UM | 37 MI 600/75   | 3<br>1 2 3      | Coupling with locking screw, solder connection                | grey<br>UM grey             | 930 764-517<br>931 110-117                |
| MAK 4100<br>MAK 4100 UM     | 37 MIBAO775 - 19 19 19 19 19 19 19 19 19 19 19 19 19   | 2 3 1 1 1 4     | Coupling with locking screw, solder connection                | grey<br>UM black<br>UM grey | 930 959-517<br>931 175-100<br>931 175-117 |









| Туре                        |  | Number of poles                      | Description                                    | Colour                      | Order no.                                 |
|-----------------------------|--|--------------------------------------|--|-----------------------------|---|
| MAK 5100<br>MAK 5100 UM     | 37. MH6x0.75   | 5<br>2<br>1<br>1<br>1<br>5           | Coupling with locking screw, solder connection | grey<br>UM black<br>UM grey | 930 960-517<br>931 176-100<br>931 176-117 |
| MAK 5100 S<br>MAK 5100 S UM | 37 M1650/75  | 5                                    | Coupling with locking screw, solder connection | grey<br>UM black<br>UM grey | 930 961-517<br>931 177-100<br>931 177-117 |
| MAK 6100<br>MAK 6100 UM     | 37 MIGNO 75 19 19 19 19 19 19 19 19 19 19 19 19 19   | 6<br>2<br>1<br>1<br>5                | Coupling with locking screw, solder connection | grey<br>UM grey             | 930 962-517<br>931 178-117                |
| MAK 7100 S<br>MAK 7100 S UM | 1 61 1 9 199 2 199 | 7<br>1<br>1<br>6<br>1<br>1<br>6<br>7 | Coupling with locking screw, solder connection | grey<br>UM grey             | 930 682-517<br>930 690-117                |
| MAK 8100 S<br>MAK 8100 S UM | 37 MR&Q.75   | 8<br>4<br>2<br>5<br>1<br>7<br>1<br>8 | Coupling with locking screw, solder connection | grey<br>UM black<br>UM grey | 930 538-517<br>931 127-100<br>931 127-117 |









| Туре           |  | Number of poles            | Description  | Colour              | Order no.                  |
|----------------|--|----------------------------|--|---------------------|----------------------------|
| MAK 8100 SN UM | 37. MH6x0.75   | 8 2 5 1 5 3 6 7            | Coupling with locking screw, solder connection                           | UM black<br>UM grey | 931 765-100<br>931 765-117 |
| MAB 3100 S     | 139<br>M18×0752<br>205<br>135<br>135<br>135<br>135<br>135<br>135<br>135<br>135<br>135<br>13  | 3                          | Panel-mounted socket with locking screw, solder connection, not shielded | black<br>grey       | 930 303-500<br>930 303-517 |
| MAB 4100       | 15 MIBS 07.2 200 200 2 200 2 200 2 200 2 200 2 200 2 200 2 200 2 200 2 200 2 200 200 2 200 2 200 2 200 2 200 2 200 2 200 2 200 2 200 2 200 2 200 200 2 200 2 200 2 200 2 200 2 200 2 200 2 200 2 200 2 200 2 200 2 | 4<br>2<br>1<br>1<br>1<br>1 | Panel-mounted socket with locking screw, solder connection, not shielded | grey                | 930 951-517                |
| MAB 5100       | 77<br>739<br>739<br>739<br>739<br>739<br>739<br>739<br>739<br>739<br>7   | 5<br>2<br>1<br>1<br>1<br>5 | Panel-mounted socket with locking screw, solder connection, not shielded | grey                | 930 952-517                |
| MAB 5100 S     | 13.9<br>M18x0.022<br>20.05<br>M18x0.022  | 5<br>1<br>1<br>1<br>3      | Panel-mounted socket with locking screw, solder connection, not shielded | black<br>grey       | 930 953-500<br>930 953-517 |









| Туре        |  | Number of poles                 | Description  | Colour        | Order no.                  |
|-------------|--|---------------------------------|--|---------------|----------------------------|
| MAB 6100    | 139<br>15<br>15<br>135<br>135<br>135<br>135<br>135<br>139  | 6<br>2<br>1<br>1<br>5           | Panel-mounted socket with locking screw, solder connection, not shielded                     | black<br>grey | 930 954-500<br>930 954-517 |
| MAB 7100 S  | 139 National | 7<br>1<br>1<br>6<br>1<br>1<br>3 | Panel-mounted socket with locking screw, solder connection, not shielded                     | grey          | 931 351-517                |
| MAB 8100 S  | 15<br>139<br>135<br>135<br>135<br>135  | 8                               | Panel-mounted socket with locking screw, solder connection, not shielded                     | grey          | 930 537-517                |
| MAB 8100 SN | 139<br>M18x02.22<br>200<br>M18x02.22   | 8                               | Panel-mounted socket with locking screw, solder connection, not shielded                     | black<br>grey | 931 749-500<br>931 749-517 |
| MAB 4100 V  | 2.6 ST   | 2 3                             | Panel-mounted socket with locking screw, for print assembly, solder connection, not shielded | grey          | 932 254-517                |









| Туре        |  | Number of poles            | Description   | Colour | Order no.   |
|-------------|--|----------------------------|---|--------|-------------|
| MAB 5100 SV | 2.6  | 5<br>1<br>1<br>2<br>3      | Panel-mounted socket with locking screw, for print assembly, solder connection, not shielded  | grey   | 932 201-517 |
| MAB 6100 V  | 2.0 Sin  | 6                          | Panel-mounted socket with locking screw, for print assembly, solder connection, not shielded  | grey   | 932 202-517 |
| MAB 7100 SV | 2.6 Sign (1) | 7                          | Panel-mounted socket with locking screw, for print assembly, solder connection, not shielded  | grey   | 932 423-517 |
| MAB 8100 SV | 2.6 S S S S S S S S S S S S S S S S S S S  | 8<br>4<br>1<br>7<br>7<br>8 | Panel-mounted socket with locking screw, for print assembly, solder connection, not shielded  | grey   | 932 203-517 |
| MAB 4500 V  | M18 x 0.75  2 d  1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0   | 2 3 1 1 1 4                | Panel-mounted socket<br>with locking screw,<br>for installation in rear<br>panels; max. 4 mm,<br>solder connection,<br>not shielded | grey   | 933 053-517 |









| Туре          |  | Number of poles                 | Description   | Colour        | Order no.                  |
|---------------|--|---------------------------------|---|---------------|----------------------------|
| MAB 5500 SV   | MIS v 0.75  1 2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0  | 5                               | Panel-mounted socket<br>with locking screw,<br>for installation in rear<br>panels; max. 4 mm,<br>solder connection,<br>not shielded | black<br>grey | 932 885-500<br>932 885-517 |
| MAB 8500 SV   | M18 x 0,75  2.6  FT 1  SQ 2  S | 8<br>4<br>2<br>5<br>1<br>7<br>8 | Panel-mounted socket<br>with locking screw,<br>for installation in rear<br>panels; max. 4 mm,<br>solder connection,<br>not shielded | grey          | 933 141-517                |
| MAB 8500 SN V | 2.6 50 50 50 50 50 50 50 50 50 50 50 50 50   | 8                               | Panel-mounted socket<br>with locking screw,<br>for installation in rear<br>panels; max. 4 mm,<br>solder connection,<br>not shielded | grey          | 933 058-517                |

