

## Eaton Series C complete molded case circuit breaker

**MDL3500WA0105S2905**

**UPC:**782114826362

### **Dimensions:**

- **Height:** .01 IN
- **Length:** .01 IN
- **Width:** .01 IN

**Weight:**.01 LB

### **Warranties:**

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### **Specifications:**

- **Amperage Rating:** 500A
- **Interrupt Rating:** 65 kAIC at 240 Vac, 50 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** MDL
- **Circuit Breaker Frame Type:** Complete breaker
- **Auxiliary Switch:** 1A-1B same side with left pigtail
- **Frame Size:** M-frame
- **Series:** Series C
- **Shunt Trip:** 110-127 Vac GF or 208-240 Vac same side right pigtail
- **Terminals:** Without terminals
- **Frame:** MDL-frame
- **Frequency Rating:** 50-60 Hz

### **Supporting documents:**

- [Application of Multi-Wire Terminals for Molded](#)

## Case Circuit Breakers

- Application of Tap Rules to Molded Case Breaker Terminals
- UL listed 100%-rated molded case circuit breakers
- StrandAble terminals product aid
- Circuit breaker motor operators product aid
- Motor protection circuit breakers product aid
- Power metering and monitoring with Modbus RTU product aid
- Plug-in adapters for molded case circuit breakers product aid
- Current limiting Series C molded case circuit breakers product aid
- Multi-wire lugs product aid
- Eatons Volume 4-Circuit Protection
- Molded case circuit breakers
- Breaker service centers
- Eaton Specification Sheet - MDL3500WA0105S2905
- MOEM MCCB product selection guide
- Series C J-Frame molded case circuit breakers time current curves
- Series C G-Frame molded case circuit breakers time current curves
- Series C F-Frame molded case circuit breakers
- Implementation of arc flash mitigating solutions at industrial manufacturing facilities

### **Certifications:**

- UL Listed

**Product compliance:** No Data