

Eaton Series C complete molded case circuit breaker

MDL3600WA0105S2905

UPC:782116008865

Dimensions:

- **Height:** 8.25 IN
- **Length:** 8.25 IN
- **Width:** 4.06 IN

Weight:.01 LB

Warranties: No Data

Specifications:

- **Amperage Rating:** 600A
- **Interrupt Rating:** 65 kAIC at 240 Vac, 50 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** MDL
- **Circuit Breaker Frame Type:** Complete breaker
- **Auxiliary Switch:** 1A-1B same side with left pigtail
- **Series:** Series C
- **Shunt Trip:** 110-127 Vac GF or 208-240 Vac same side right pigtail
- **Terminals:** Without terminals
- **Frame:** MDL-frame
- **Frequency Rating:** 50-60 Hz

Supporting documents:

- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [UL listed 100%-rated molded case circuit breakers](#)
- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)

- [Motor protection circuit breakers product aid](#)
- [Circuit breaker motor operators product aid](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Multi-wire lugs product aid](#)
- [StrandAble terminals product aid](#)
- [Power metering and monitoring with Modbus RTU product aid](#)
- [Current limiting Series C molded case circuit breakers product aid](#)
- [Molded case circuit breakers](#)
- [Eaton's Volume 4-Circuit Protection](#)
- [Breaker service centers](#)
- [Eaton Specification Sheet - MDL3600WA0105S2905](#)
- [MOEM MCCB product selection guide](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)
- [Series C F-Frame molded case circuit breakers time current curves](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)
- [Implementation of arc flash mitigating solutions at industrial manufacturing facilities](#)

Certifications:

- [UL Listed](#)

Product compliance: No Data