

Eaton Series C complete molded case circuit breaker

MDL3800FA13K14T14

UPC:782116681174

Dimensions:

- **Height:** .01 IN
- **Length:** .01 IN
- **Width:** .01 IN

Weight:.01 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Frame only
- **Amperage Rating:** 800A
- **Interrupt Rating:** 65 kAIC at 240 Vac, 50 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Electronic LSIG
- **Circuit Breaker Type:** MDL
- **Auxiliary Switch:** 2A-2B rear with right pigtail
- **Frame Size:** M-frame
- **Series:** Series C
- **Undervoltage Release:** 110-125 Vdc rear with left pigtail
- **Frame:** MDL-frame

Supporting documents:

- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [UL listed 100%-rated molded case circuit](#)

breakers

- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Multi-wire lugs product aid](#)
- [Current limiting Series C molded case circuit breakers product aid](#)
- [Circuit breaker motor operators product aid](#)
- [Motor protection circuit breakers product aid](#)
- [StrandAble terminals product aid](#)
- [Power metering and monitoring with Modbus RTU product aid](#)
- [Molded case circuit breakers](#)
- [Eaton's Volume 4-Circuit Protection](#)
- [Breaker service centers](#)
- [MOEM MCCB product selection guide](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)
- [Eaton Specification Sheet - MDL3800FA13K14T14](#)
- [Series C F-Frame molded case circuit breakers](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)
- [Implementation of arc flash mitigating solutions at industrial manufacturing facilities](#)

Certifications:

- [UL Listed](#)

Product compliance: No Data