

## Eaton Series C complete molded case circuit breaker

**MDL3800WS02**

**UPC:**782116008841

### **Dimensions:**

- **Height:** .01 IN
- **Length:** .01 IN
- **Width:** .01 IN

**Weight:**.01 LB

### **Warranties:**

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### **Specifications:**

- **Amperage Rating:** 800A
- **Interrupt Rating:** 65 kAIC at 240 Vac, 50 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** MDL
- **Circuit Breaker Frame Type:** Complete breaker
- **Frame Size:** M-frame
- **Series:** Series C
- **Shunt Trip:** 12-24 Vac/dc rear with left pigtail shunt
- **Terminals:** Without terminals
- **Frame:** MDL-frame

### **Supporting documents:**

- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [UL listed 100%-rated molded case circuit breakers](#)

- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Motor protection circuit breakers product aid](#)
- [Current limiting Series C molded case circuit breakers product aid](#)
- [Circuit breaker motor operators product aid](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Multi-wire lugs product aid](#)
- [StrandAble terminals product aid](#)
- [Power metering and monitoring with Modbus RTU product aid](#)
- [Eaton's Volume 4-Circuit Protection](#)
- [Molded case circuit breakers](#)
- [Breaker service centers](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)
- [MOEM MCCB product selection guide](#)
- [Series C F-Frame molded case circuit breakers](#)
- [Eaton Specification Sheet - MDL3800WS02](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)

**Certifications:**

- [UL Listed](#)

**Product compliance:** No Data