

Eaton Series C complete molded case circuit breaker

MDL3800Z03

UPC:782116063918

Dimensions:

- **Height:** .01 IN
- **Length:** .01 IN
- **Width:** .01 IN

Weight:.01 LB

Notes:TA801MA terminals

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Amperage Rating:** 800A
- **Interrupt Rating:** 65 kAIC at 240 Vac, 50 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** MDL
- **Circuit Breaker Frame Type:** Complete breaker
- **Frame Size:** M-frame
- **Series:** Series C
- **Terminals:** Optional line and load
- **Frame:** MDL-frame

Supporting documents:

- [UL listed 100%-rated molded case circuit breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)

- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Current limiting Series C molded case circuit breakers product aid](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [StrandAble terminals product aid](#)
- [Circuit breaker motor operators product aid](#)
- [Power metering and monitoring with Modbus RTU product aid](#)
- [Motor protection circuit breakers product aid](#)
- [Multi-wire lugs product aid](#)
- [Eatons Volume 4-Circuit Protection](#)
- [Molded case circuit breakers](#)
- [Breaker service centers](#)
- [MOEM MCCB product selection guide](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)
- [Series C F-Frame molded case circuit breakers](#)
- [Eaton Specification Sheet - MDL3800Z03](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)

Certifications:

- [UL Listed](#)

Product compliance: No Data