

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Range	PowerLogic
Product name	PowerLogic PM3000
Device short name	PM3250
Product or component type	Power meter

Complementary

Power quality analysis	Up to the 15th harmonic
Device application	Multi-tariff Power monitoring Sub billing
Type of measurement	Active and reactive power Apparent power Current Voltage Energy Power factor Frequency Total current harmonic distortion THD (I) Total voltage harmonic distortion THD (U)
Supply voltage	100...277 V AC 45...65 Hz 173...480 V AC 45...65 Hz 100...300 V DC
Network frequency	60 Hz 50 Hz
Line Rated Current	5 A 1 A
Type of network	1P + N 3P 3P + N
Power consumption in VA	5 VA
Display type	Backlit LCD
Display resolution	128 x 96 pixels
Sampling rate	32 samples/cycle
Measurement current	0.02...1.2 A 0.05...6 A
Analogue input type	Current 0...5 A Current 0...1 A
Measurement voltage	50...330 V AC 45...65 Hz direct 50...330 V AC 45...65 Hz phase to neutral 80...570 V AC 45...65 Hz direct 80...570 V AC 45...65 Hz phase to phase 570...999000 V AC 45...65 Hz with external VT
Frequency measurement range	45...65 Hz
Number of inputs	0
Measurement accuracy	Current 0.3 % 0.5...6 A Current 0.5 % 0.1...1.2 A Voltage 0.3 % 50...330 V Voltage 0.3 % 80...570 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Accuracy class	Class 0.5S active energy IEC 62053-22 Class 1 active energy IEC 62053-21 Class 2 reactive energy IEC 62053-23 Class C active energy EN 50470-3
Number of outputs	0
Information displayed	Tariff 4)
Communication port protocol	Modbus 9.6...38.4 kbauds
Communication port support	RS485
Data recording	Time stamping Min/Max of instantaneous values 5 alarms
Mounting mode	Clip-on
Mounting support	DIN rail
Standards	IEC 61557-12 EN 50470-3 EN 61010-1 EN 50470-1 EN 61557-12 UL 61010-1 IEC 62052-11
Product certifications	CE EN 61010-1 CULus UL 61010-1 UL
Width	3.54 in (90 mm)
Depth	2.76 in (70 mm)
Height	3.74 in (95 mm)
Product weight	0.57 lb(US) (0.26 kg)

Environment

Electromagnetic compatibility	Electrostatic dischargelevel 4 IEC 61000-4-2 Susceptibility to electromagnetic fieldslevel 3 IEC 61000-4-3 Electrical fast transient/burst immunity testlevel 4 IEC 61000-4-4 1.2/50 μ s shock waves immunity testlevel 4 IEC 61000-4-5 Conducted RF disturbanceslevel 3 IEC 61000-4-6 Magnetic field at power frequency 0.5 mT IEC 61000-4-8 Conducted and radiated emissionsclass B EN 55022
Overvoltage category	III
IP degree of protection	Front panel IP40 IEC 60529 Body IP20 IEC 60529
Relative humidity	5...95 % 122 °F (50 °C)
Pollution degree	2
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Operating altitude	0...9842.52 ft (0...3000 m)

Ordering and shipping details

Category	09786 - SE ENTRY POWER METER
Discount Schedule	PL1
GTIN	00785901009979
Package weight(Lbs)	0.04 kg (0.08 lb(US))
Returnability	No
Country of origin	CN

Contractual warranty

Warranty	18 months
----------	-----------