



Main

Range	PowerLogic
Product or component type	I/O module
Device application	Optional expansion module
Range compatibility	PowerLogic (PowerLogic PM8000) PowerLogic (PowerLogic ION7400) PowerLogic (PowerLogic ION9000)

Complementary

Number of outputs	2 analog, 0-20 mA or 4-20 mA or 0...10 V
Number of inputs	4 analog 0...20 mA/4...20 mA 0...30 V
Width	22 mm
Depth	90.5 mm
Height	90.5 mm
Net weight	140 g

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
IP degree of protection	IP30 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6 cm
Package 1 Width	10 cm
Package 1 Length	12 cm
Package 1 Weight	223 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty

18 Monate
