



# Scotchmate™ and Dual Lock™ Reclosable Fasteners Mini-Packs

MP3401/02, MP3526N/27N, MP3541/42,  
MP3551/52, MP3560, MP4570

## Selection Guide

March, 2005

### Product Description

3M™ Reclosable Fasteners offer advanced closure alternatives to zippers, screws, snaps, bolts and more. They're often better than conventional closure methods because they offer greater design flexibility, faster product assembly, smoother and cleaner exterior surfaces and improved product performance in many applications.

3M™ Scotchmate™ and Dual Lock™ Reclosable Fasteners Mini-Packs are great for design development and small volume product requirements and can be used to inexpensively test and evaluate eight most popular 3M reclosable fasteners before making a more substantial investment.

### Features

- Simplifies storage and dispensing.
- Available in both plain-backed and adhesive-backed fasteners.
- Faster, easier attachment.
- Pressure-sensitive adhesive-backed versions include both general purpose synthetic rubber and 3M™ High Performance Acrylic Adhesives.

### Construction

#### 3M™ Scotchmate™ Hook and Loop Reclosable Fasteners

| Product/Color     | Roll Size      | Qty per pkg      | Description                                                  | Attachment Method                      |
|-------------------|----------------|------------------|--------------------------------------------------------------|----------------------------------------|
| MP3401/02 white   | 1 in x 4.9 yds | 1 hook<br>1 loop | Plain-back 3M™ Scotchmate™ Reclosable Fastener               | Sew-on, staple or mechanical           |
| MP3401/02 black   | 1 in x 4.9 yds | 1 hook<br>1 loop | Plain-back 3M™ Scotchmate™ Reclosable Fastener               | Sew-on, staple or mechanical           |
| MP3526N/27N white | 1 in x 4.9 yds | 1 hook<br>1 loop | General Purpose Synthetic Rubber Pressure Sensitive Adhesive | Adhesive bonds well to most substrates |
| MP3526N/27N black | 1 in x 4.9 yds | 1 hook<br>1 loop | General Purpose Synthetic Rubber Pressure Sensitive Adhesive | Adhesive bonds well to most substrates |

#### 3M™ Dual Lock™ Reclosable Fasteners

| Product/Color                       | Roll Size        | Qty per pkg          | Description                                                                    | Attachment Method                                     |
|-------------------------------------|------------------|----------------------|--------------------------------------------------------------------------------|-------------------------------------------------------|
| MP3541/42 black with black adhesive | 1 in x 4.9 yds   | 1 - 3541<br>1 - 3542 | General Purpose Synthetic Rubber Pressure Sensitive Adhesive                   | Adhesive bonds well to most substrates                |
| MP3551/52 black with white adhesive | 1 in x 4.9 yds   | 1 - 3551<br>1 - 3552 | High Performance Acrylic Foam Pressure Sensitive Adhesive                      | Adhesive bonds well to high surface energy substrates |
| MP3560 clear with clear adhesive    | 1 in x 4.9 yds   | 2 - 3560             | CLEAR 3M™ Dual Lock™ High Performance Acrylic Foam Pressure Sensitive Adhesive | Adhesive bonds well to high surface energy substrates |
| MP4570 clear with clear adhesive    | 5/8 in x 10 feet | 1 - 4570             | CLEAR 3M™ Dual Lock™ Low Profile with Acrylic LSE Adhesive                     | Adhesive bonds well to low surface energy substrates  |

# 3M™ Scotchmate™ and 3M™ Dual Lock™ Reclosable Fasteners Mini-Packs

MP3401/02, MP3526N/27N, MP3541/42, MP3551/52, MP3560, MP4570

---

## Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

---

## Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

---

## Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

---

ISO 9001:2000 - ISO/TS 16949:2002

---

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 and ISO/TS 16949:2002 standards.



### Industrial Business Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue  
St. Paul, MN 55144-1000  
800-362-3550 • 877-369-2923 (fax)  
www.3M.com/industrial



Recycled Paper  
40% pre-consumer  
10% post-consumer

Printed in U.S.A.  
©3M 2005 70-0709-3865-2 (3/05)