

NL10276BC20-18D

10.4" XGA
Industrial use
[Features]

- High contrast (900:1)
- 16.77M/262K colors (LVDS RGB 8-bit/6-bit)
- Wide temperature (-30°C to +80°C)
- Reversible-scan direction
- Long-life LED backlight*1



Pixel	1,024(H) x 768(V)
Display area	210.432(H) x 157.824(V) mm 10.4inches (26cm)
Display color	16,777,216 colors/ 262,144 colors
Pixel pitch	0.2055(H) x 0.2055(V) mm
Luminance	400cd/m ² (typ.)
Contrast ratio	900:1 (typ.)
Viewing angle※2	Up: 80°,Down: 80°,Left: 80°,Right: 80°
Response time※3	18ms (typ.)
Signal system	LVDS 1-port RGB 8-bit/6-bit
Power supply voltage	3.3V
Power consumption	4.8W (typ.)
Operating temperature	-30°C to +80°C
Storage temperature	-30°C to +80°C
Polarizer surface	Antiglare
Module size	228.0 (typ.) x 178.5 (typ.) x 9.2 (max.) mm
Weight	380g (typ.)
Backlight	LED backlight(Replaceable)
LED driver	104PW02F

※1 70k hours long life LED

※2: Contrast ratio ≥ 10:1

※3: Ton+Toff (10%←→90%)

※All information is subject to change without notice.

※Screen images are simulated.

<NLT Technologies web site>
Japanese <http://www.nlt-technologies.co.jp/jp>
English <http://www.nlt-technologies.co.jp/en>

Last update:11/2015

©NLT Technologies,Ltd. 2011-2015