

PRODUCTS

Chilisin provides inductor turnkey solutions for EMI, power and RF and a global technical team to support its customers. Chilisin has become one of the few inductor suppliers capable of providing a complete "one-stop shopping" experience.



Products Line

- Power Inductor
- Chip Inductor
- Bead
- Common Mode Choke
- ◆ Product Search

NL252018

Home > Products > Chip Inductor > NL252018



Part Number : NL252018T-1R0?-N

Structure	Wire Wound
Size Code(JIS/EIA)	2520/1008
Inductance	1
Unit	uH
Tolerance(±%)	10,5
Test Frequency(L)	7.96MHz
Q Min	25
Test Frequency(Q)	7.96MHz
SRF(MHz)Min	245
RDC(?)Max	1.1
IDC(mA)	800
Operating Temperature	- 2 5℃~ 1 0 5℃(Including self - temperature rise)
L(mm)	2.92Max.
W(mm)	2.50Max.
T(mm)	2.20Max.

1.IDC:Applied the current to coils the inductance shall be less than 10% initial value.
2.L/Q Test OSC@200mV

P/N	NL252018T-1R0J-N
Part Numbering	
Dimensions	
Packing	
Recommended Pattern	
Electrical Characteristics Curve	

[Back](#)