

# PRODUCTS

Chilisin provides inductor turnkey solutions for EMI, power and RF and a global technical team to support its customers. Chilisin has become one of the few inductor suppliers capable of providing a complete "one-stop shopping" experience.



**Products Line**

- Power Inductor
- Chip Inductor
- Bead
- Common Mode Choke

**Product Search**



**NLC322522**

Home > Products > Chip Inductor > NLC322522



**Part Number : NLC322522T-5R6?-N**

Structure	Wire Wound
Size Code(JIS/EIA)	3225/1210
Inductance	5.6
Unit	uH
Tolerance(±%)	10,5
Test Frequency(L)	7.96MHz
Q Min	20
Test Frequency(Q)	7.96MHz
RDC(ohm)	0.26
RDC Tolerance(±%)	30
IDC(mA)	620
Operating Temperature	- 2 5 °C ~ 1 0 5 °C (Including self - temperature rise)
L(mm)	3.70Max.
W(mm)	2.90Max.
T(mm)	2.60Max.

1.IDC:Applied the current to coils  
the inductance shall be less than 10% initial value.

P/N	NLC322522T-5R6J-N
Part Numbering	
Dimensions	
Packing	  
Recommended Pattern	
Electrical Characteristics Curve	 

[Back](#)