

Expandable Braided Sleeving Nomex®



Description

A flexible tubular expandable sleeving, braided with Nomex (polyaryl-mide) multifilament fibres. This light weight braided product exhibits an exceptional thermal stability and chemical, solvent and abrasion resistance.

The sleeving retains its integrity at temperatures over 245°C, (the melting point of Nylon) or in presence of Beta, gamma and X-ray radiation or when exposed to high humidity or moisture.

The expandable construction allows the sleeving to be easily drawn on long lengths of wiring and cover a wide range of diameters with only a few product sizes. Used for a wide range of applications such as military and aerospace wiring and harnessing applications. Low smoke, low toxicity and halogen free.

Specifications:

Colour	: Olive
Material	: Nomex (Polyaryl-mide)
Operating Temperature	: -50°C to +150°C
Tensile Strength at Break	: Conditioned at 65%. RH: 4.4cN/dtex. Wet: 3.5cN/dtex
Elongation at Break	: Conditioned at 65%. RH: 25%. Wet: 16%
Initial Modulus at 100% Elongation:	Conditioned at 65%. RH: 110cN/detex
Fibre	: 200 Derniers (220 dtex)
Specific Gravity	: 1.38
Coefficient of Linear Expansion (21-204°C) after	
Relaxed Heat-Setting at 260°C	: 2 × 10-8cm (cm/°C)
Thermal Conductivity	: 0.13W (m.K)
Flame Resistance	: Nomex does not melt or flow till 371°C UL94-V0
Chemical Resistance	: Mineral Acids,Organic Acids, Alkalis, Cleaning Agents, Salt Solutions, Unaffected by Freon, Gasoline, Jet Fuel, Ethylene Glycol and Methyl Alcohol
Standards	: MIL-C-43435B

Part Number Table

Description	Diameter		Colour	Reel Length	Part Number
	Minimum	Maximum			
Expandable Braided Sleeving Nomex®	4mm	8mm	Olive	100m (328 ft.)	NOMEX60EDB100R
	5mm	12mm		50m (164 ft.)	NOMEX80EDB50R
	8mm	16mm			NOMEX10OEDB50R
	10mm	20mm			NOMEX15OEDB50R
	12mm	24mm			NOMEX20OEDB50R

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell Limited 2016.