



# NP24-12

Valve Regulated Lead-Acid (VRLA)  
Absorbed Glass Mat (AGM)

Yuasa NP/NPX Series with **HT X Alloy™**, high temperature batteries optimized for performance and life

## SPECIFICATIONS

Battery Model:	NP24-12
Nominal Voltage:	12
Capacity: 20-hr rate, 1.75vpc @ 25°C (77°F)	24.0 Ah
Case Material Options:	UL94HB UL94V-0 (FR)
Terminal Options:	M5 Bolt & Nut Faston .250 in. (F2) M5 Recessed Post
Terminal Torque (Terminals using Bolts):	2.6Nm (23 in-lb)
Dimensions:	
◦ Length (mm inches)	166.0   6.54
◦ Width (mm inches)	175.0   6.89
◦ Case Height (mm inches)	125.0   4.92
◦ Height over Terminal (mm inches)	125.0   4.92
Weight (kg lbs):	8.30   18.30
Short circuit current (A):	770 (* .250 terminal 460A)
Max charge current (A):	6.000
Internal Resistance (mΩ):	~9.0






## GENERAL

Design Life:	4-6 Years
Storage:	
◦ Capacity loss per month at 25°C (77°F)	~3%
Operating Temperature Range:	
◦ Storage (in fully charged condition)	-20°C to 60°C (-4°F to 140°F)
◦ Charge	-15°C to 50°C (5°F to 122°F)
◦ Discharge	-20°C to 60°C (-4°F to 140°F)
Float Charge Voltage:	
◦ Charge voltage at 25°C (77°F)	2.275±1%/cell
◦ Temperature correction factor from 25°C (77°F)	-3mV per °C/cell
Cyclic (or Boost) Charge Voltage	
◦ Cyclic voltage at 25°C (77°F)	2.45±2%/cell
◦ Temperature correction factor from 25°C (77°F)	-4mV per °C/cell

## CERTIFICATIONS/COMPLIANCE

- ISO 9001
- ISO 14001
- IEC 61056-1
- IEC 60896-21
- UL recognized component, UL1989
- TAA Compliant - Available
- DRC Conflict Free

## TERMINAL OPTIONS



### Features providing longer life:

- HT X Alloy™**
- Proprietary Additives
- Lead Calcium Grids
- Primary Lead
- Strategic use of Tin
- Optimized AGM Separators

### Applications:

- Security Systems
- Fire Protection & Life Safety
- Emergency Lighting
- Uninterruptible Power Supply (UPS)
- Solar & Wind Support Systems
- Power Packs

*Non-spillable, meets or exceeds DOT and IATA requirements for non-hazardous transportation*




(800) 472-2879  
www.gsyuasa-es.com  
sales@gsyuasa-es.com

GS Yuasa Energy Solutions, Inc  
1150 Northmeadow Pkwy, Suite 110  
Roswell, GA 30076



# NP24-12

Valve Regulated Lead-Acid (VRLA)  
Absorbed Glass Mat (AGM)



Discharge, Watts @ 25°C (77°F)												
End vpc	5m	10m	15m	30m	1h	1.5h	2h	3h	5h	8h	10h	20h
1.80vpc	909	690	538	329	192	134	106	74.0	50.3	32.1	26.5	14.4
1.75vpc	980	733	559	339	195	136	107	74.6	50.7	32.3	26.7	14.4
1.67vpc	1,048	753	569	342	197	137	108	75.4	51.2	32.6	27.0	14.6
1.60vpc	1,100	764	574	345	197	138	109	76.3	51.8	33.1	27.4	14.8

\*.250 (F2) Terminal, anything less than a 1 hour discharge is for sizing only. Consult with GYES

Discharge, Amps @ 25°C (77°F)												
End vpc	5m	10m	15m	30m	1h	1.5h	2h	3h	5h	8h	10h	20h
1.80vpc	81.0	60.0	46.0	28.3	16.3	11.4	8.90	6.17	4.19	2.67	2.20	1.19
1.75vpc	89.0	65.0	48.0	29.2	16.6	11.5	9.00	6.23	4.24	2.69	2.22	1.20
1.67vpc	96.0	67.5	49.2	29.7	16.7	11.6	9.12	6.27	4.27	2.71	2.24	1.21
1.60vpc	103	69.0	50.0	29.9	16.8	11.7	9.20	6.36	4.32	2.75	2.27	1.22

\*.250 (F2) Terminal, anything less than a 1 hour discharge is for sizing only. Consult with GYES

### Long Shelf Life

The extremely low self discharge rate allows the battery to be stored for extended periods, up to one year at normal ambient temperatures with no permanent loss of capacity

Order Number:	Terminal   Case Material
NP24-12B	M5 Bolt & Nut   UL94HB
NP24-12BFR	M5 Bolt & Nut   UL94V-0 (FR)
NP24-12-250	Faston .250 in. (F2)   UL94HB
NP24-12-250FR	Faston .250 in. (F2)   UL94V-0 (FR)
NP24-12R	M5 Recessed Post   UL94HB
NP24-12RFR	M5 Recessed Post   UL94V-0 (FR)

Distributed By:



WARNING: Cancer and Reproductive Harm. Wash hands after handling. [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



(800) 472-2879  
www.gsyuasa-es.com  
sales@gsyuasa-es.com

GS Yuasa Energy Solutions, Inc  
1150 Northmeadow Pkwy, Suite 110  
Roswell, GA 30076  
MKT-085 NP24-12 Spec Sheet ver. 1.0 08-2025