

4, 5, 6, 8 10 and 12-Wire M12 eurofast® Receptacles, Front Mount, 1/2-14 NPT Threads

- Female Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Drawing Number	Part Number	Lead Specs.	Application	Pinout
<p>8 FK .. /14.5/NPT</p>	FK 4.4-*/14.5/NPT	UL, CSA 4x22 AWG 105°C 300 V, 4 A	Mates with 4-pin Cordsets	1. BN 2. WH 3. BU 4. BK
	FK 4.4-*/14.5/NPT/S613	UL, CSA 4x18 AWG 105°C 250 VAC/VDC 4 A	Mates with 4-pin Cordsets	1. BN 2. WH 3. BU 4. BK
	FK 4.5-*/14.5/NPT	UL, CSA 5x22 AWG 105°C 250 V, 4 A	Mates with 5-pin Cordsets	1. BN 2. WH 3. BU 4. BK 5. GY
	FK 6-*/14.5/NPT	UL, CSA 6x24 AWG 105°C 250 V, 4 A	Mates with 6-pin Cordsets	1. BN 2. WH 3. BU 4. BK 5. GY 6. PK
	FK 8-*/14.5/NPT	UL, CSA 8x24 AWG 105°C 250 V, 4 A	Mates with 8-pin Cordsets	1. WH 5. GY 2. BN 6. PK 3. GN 7. BU 4. YE 8. RD
	FK 8.6-*/14.5/NPT	UL, CSA 6x24 AWG 105°C 60 VAC/75 VDC 2 A	Mates with 8-pin Cordsets	1. WH 5. BN 2. GN 6. N/C 3. YE 7. BU 4. GY 8. N/C
	FK 10-*/14.5/NPT	UL, CSA 10x24 AWG 105°C 60 VAC/75 VDC 2 A	Mates with 10-pin Cordsets	1. WH 6. PK 2. BN 7. BU 3. GN 8. RD 4. YE 9. OG 5. GY 10. TN
	FK 12-*/14.5/NPT	UL, CSA 12x24 AWG 105°C 60 VAC/75 VDC 2 A	Mates with 12-pin Cordsets	1. WH 7. BU 2. BN 8. RD 3. GN 9. OG 4. YE 10. TN 5. GY 11. BK 6. PK 12. VT

Receptacles

See page D113 for dimensional drawings.

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.
Standard housing material is nickel plated brass "FK."; "FKV.." indicates 316 stainless steel.
To specify PVC jacketed cable, add "/S717" to the end of the part number.