



## Overview

Lead time	Usually Ships within 4 Weeks
-----------	------------------------------

## Main

Range	ClimaSys
Product name	ClimaSys CC
Product or component type	Electronic hygrotherm
Temperature setting range	-40...80 °C
Humidity setting range	20...80 %
Display type	OLED screen
Information displayed	Relative humidity Temperature in °F Temperature in °C

## Complementary

Input voltage	200...240 V AC
Sensor type	Optional NTC external sensor
Maximum switching capacity	4 A 230 V AC
Electrical connection	8 connectors, clamping capacity: 2.5 mm <sup>2</sup>
Mounting mode	Clipped By screws
Height	85 mm external:
Width	56 mm external:
Depth	44 mm external:
Mounting location	35 mm DIN rail Cross rails Spacial upright On mounting plate
Ambient air temperature for operation	-40...80 °C
Hysteresis	2 K programmed value
Hysteresis	3 %
Number of outputs	2 ventilation/heating function
Material	PC
Colour	Light grey
Flame retardance	Self-extinguishing conforming to UL94 (material V0)
Product certifications	UR

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.096 cm
Package 1 Width	8.128 cm
Package 1 Length	8.89 cm
Package 1 Weight	149.687 g
Unit Type of Package 2	CAR
Number of Units in Package 2	75
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	12 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------