



### Main

Range	ClimaSys
Product name	ClimaSys CR
Product or component type	Resistance heater
Range compatibility	Prisma (P) Prisma (G)
Power range	55 W
Input voltage	110...250 V AC 50/60 Hz

### Complementary

Operating position	Vertical
Ambient air temperature for operation	-40...70 °C
IP degree of protection	IP20
Product certifications	UL VDE
Material	Body: extruded aluminium
Height	200 mm
Width	85 mm
Depth	70 mm
Condition of use	Air sealed enclosure Heaters must be installed with a thermal controller Electrical protection is needed
Fixing mode	By clips
Mounting support	35 mm DIN rail

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7 cm
Package 1 Width	8 cm
Package 1 Length	20.5 cm
Package 1 Weight	534 g
Unit Type of Package 2	CAR
Number of Units in Package 2	16
Package 2 Height	42 cm
Package 2 Width	34 cm
Package 2 Length	16 cm
Package 2 Weight	9.16 kg
Unit Type of Package 3	P12
Number of Units in Package 3	480
Package 3 Height	93 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	288.5 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------