

Eaton Series C complete molded case circuit breaker

JG3225A05S41

UPC:782116018772

Dimensions:

- **Height:** 7 IN
- **Length:** 12 IN
- **Width:** 7 IN

Weight:9.21 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Amperage Rating:** 225A
- **Interrupt Rating:** 14 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac
- **Trip Type:** Thermal-magnetic
- **Circuit Breaker Frame Type:** Complete breaker
- **Class:** Engine generator
- **Auxiliary Switch:** 1A-1B same side with right pigtail
- **Shunt Trip:** 12-24 Vac/dc same side with left pigtail shunt
- **Terminals:** Line and load
- **Frame:** J-frame
- **Frequency Rating:** 60 Hz
- **Feed Type:** Reverse
- **Generator Rating:** 81 kVA/65 kW at 240 Vac, 162 kVA/130 kW at 480 Vac, 203 kVA/162 kW at 600 Vac

Supporting documents:



- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [UL listed 100%-rated molded case circuit breakers](#)
- [Circuit breaker motor operators product aid](#)
- [Current limiting Series C molded case circuit breakers product aid](#)
- [StrandAble terminals product aid](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Motor protection circuit breakers product aid](#)
- [Power metering and monitoring with Modbus RTU product aid](#)
- [Multi-wire lugs product aid](#)
- [Eatons Volume 4-Circuit Protection](#)
- [Molded case circuit breakers](#)
- [Series C Engine Generator Circuit Breakers - Dimension Sheets](#)
- [Breaker service centers](#)
- [Eaton Specification Sheet - JG3225A05S41](#)
- [Series C F-Frame molded case circuit breakers](#)
- [MOEM MCCB product selection guide](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)

Certifications:

- UL Listed
- IEC Rated
- IEC 947-2
- CSA Certified
- UL 489
- CSA Std. C22.2 No. 5

Product compliance: No Data