

# PME271M622KR19T0

aka P276CP224K275L

Capacitor, film, 0.22 uF, +/-10% Tol, -40/+110C, Safety: X2, 275VAC,  
Lead Spacing=20.3 mm



## Dimensions (mm)

## Specifications

ID	Dimension	Tolerance	Manufacturer:	KEMET
L	24	max	Brand:	Rifa
H	16.5	max	Capacitance:	0.22 uF
T	11.3	max	Temperature Range:	-40/+110C
S	20.3	+/-0.4	Rated Temperature:	110C
LL	19	nom	Voltage @ rated temp:	630V
F	0.8	nom	Voltage AC:	275VAC
			Tolerance:	+/-10%
			Body Type:	Radial Molded
			Construction:	Wound
			Application:	Safety: X2
			Dissipation Factor @ 1 kHz:	1.3%
			Insulation Resistance:	12 GOhm
			Maximum dVdT:	600v/us
			UL_1414:	250V
			UL_1283:	250V
			IEC_60384-14:	275V
			EN_132400:	275V
			C_22.2_NO.1:	250V
			Miscellaneous Electrical:	f <sub>o</sub> = 2.7 MHz series(PME271M)
			Package Kind:	T&R
			Package Size:	360mm
			Package Quantity:	180