



FEATURES:

- Mounts in panels from 1.57 (.062) to 3.18 (.125) thick.
- Complies to MIL-P-55149/8.

MATERIALS:

Body: Nickel plated brass

“O” Rings and Cap: Silicon rubber

Finish: Gold plated brass

Hardware: Hex nut, Split lockwasher, Brass washer, Nylon washer, “O” Rings, Body, Cap

Markings: “PB08NA01” for Black Binding Posts

“PB08NA02” for Red Binding Posts

RATINGS:

Voltage: Hand-held testing: 30VAC/60VDC Max.

Hands free testing in controlled voltage environments: 1200 WVDC Max.

Operating Temperature: +115°C (+239°F) Max.

Current: 15 Amperes

ORDERING INFORMATION: Model 4995-*

*=Color, -0 Black, -2 Red only

Ordering Example: 4995-2 Color is Red

All dimensions are in inches. Tolerances (except noted): .xx = ±.02” (.51 mm), .xxx = ±.005” (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

[4995-0](#) [4995-2](#)