

Product availability: Stock - Normally stocked in distribution facility



### Main

Product line	QO
Product type	Load Center Grounding Bar

### Complementary

Number of connectors	24
Wire size	AWG 14...AWG 4 copper AWG 12...AWG 4 aluminium AWG 4...AWG 1 aluminium/copper
Provided equipment	2 screw
Bar length	9.45 in (240 mm)
Maximum length of segment	3.15 in (80 mm)
Device mounting	Direct mounting back of enclosure
Tightening torque	2.26 N.M (20 lbf.in) AWG 14...AWG 10) 2.26 N.M (20 lbf.in) AWG 12...AWG 10) 3.95 N.M (35 lbf.in) AWG 6...AWG 4) 2.82 N.M (25 lbf.in) AWG 8) 2.82 N.M (25 lbf.in) AWG 14...AWG 12) 2.82 N.m (25 lbf.in) AWG 12...AWG 10)

### Ordering and shipping details

Category	00102 - QO LC ACCESSORIES
Discount Schedule	DE3A
GTIN	00785901440895
Package weight(Lbs)	0.18 kg (0.4 lb(US))
Returnability	Yes
Country of origin	US

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

---

Warranty	18 months
----------	-----------

---