



Cable Tie, Black, UV Nylon 612, 3.9", 20lb, PK1000

PLT1M-M6120

Panduit PLT1M-M6120 Locking Cable Ties are designed to satisfy the needs of solar applications and resistance to corrosive elements such as zinc chloride, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Miniature cross section, 3.9" (99mm) length. Made of Weather Resistant Nylon 612 with high resistance to ultraviolet light, are black in color and come in packages of 1000.

Specifications

Product Type	Cable Ties
Sub Brand	Pan-Ty®
Color	Black
Environment	Harsh/Indoor/Outdoor
Material	Weather Resistant Nylon 612
Resistance Properties	Chemical and UV Resistant
Overall Length (In.)	3.9
Overall Length (mm)	99
Body Width (In.)	0.098
Body Width (mm)	2.5
Body Thickness (In.)	0.043
Body Thickness (mm)	1.1
Maximum Bundle Diameter (In.)	0.87
Maximum Bundle Diameter (mm)	22
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	89
Minimum Loop Tensile Strength (lb)	20
Maximum Operating Temperature (°C)	90
Maximum Operating Temperature (°F)	194
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	RoHS CE / UKCA

Specifications (continued)

For Use With	GTS-E, GS2B-E, PTS, PPTS, STS2
--------------	--------------------------------

Packaging Detail

UPC	61305684510
Std. Pkg. Qty.	1000
Std. Pkg. Volume (cf)	0.0912
Std. Ctn. Qty.	50000
Std. Ctn. Volume (cf)	4.5618