



## Cable Tie, Black, UV Nylon 612, 11.5", 50lb, PK1000

PLT3S-M6120

Panduit PLT3S-M6120 Locking Cable Ties are designed to satisfy the needs of solar applications, and resistance to corrosive elements such as zinc chloride applications, while delivering consistent performance and reliability. Cable tie of choice for making attachments to galvanized surfaces. Standard cross section, 11.5" (292mm) length. Made of Weather Resistant Nylon 612 with high resistance to ultraviolet light, are black in color and come in packages of 1000

### Specifications

Product Type	Cable Ties
Sub Brand	Pan-Ty®
Color	Black
Environment	Harsh/Indoor/Outdoor
Material	Weather Resistant Nylon 612
Resistance Properties	Chemical and UV Resistant
Overall Length (In.)	11.5
Overall Length (mm)	292
Body Width (In.)	0.19
Body Width (mm)	4.8
Body Thickness (In.)	0.052
Body Thickness (mm)	1.3
Maximum Bundle Diameter (In.)	3
Maximum Bundle Diameter (mm)	76
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	222
Minimum Loop Tensile Strength (lb)	50
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	RoHS CE / UKCA

**Specifications (continued)**

For Use With	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2
--------------	----------------------------------------------------------

**Packaging Detail**

UPC	61305684518
Std. Pkg. Qty.	1000
Std. Pkg. Volume (cf)	0.3345
Std. Ctn. Qty.	10000
Std. Ctn. Volume (cf)	3.3446