

KEMET Part Number: PME278RA4100MR30
(P278HE102M440A)

PME278/P278, Film, Metallized Paper, Safety, 1000 pF, 20%, 440 VAC (X1), 1000 VDC, 110°C, Lead Spacing = 10.2mm



Dimensions

L	13.5mm MAX
H	7.5mm MAX
T	3.9mm MAX
S	10.2mm +/-0.4mm
LL	30mm +5mm
F	0.6mm +/-0.05mm

Packaging Specifications

Packaging:	Bulk, Bag
Packaging Quantity:	1000

General Information

Series:	PME278/P278
Dielectric:	Metallized Paper
Style:	Radial
Features:	EMI Safety
RoHS:	Yes
Lead:	Wire Leads
Qualifications:	ENEC
AEC-Q200:	No
Construction:	Molded
Miscellaneous:	SRF= 53 MHz.
Notes:	Not For New Design, Please Use The New P278 Series @ 480 VAC.

Specifications

Capacitance:	1000 pF
Capacitance Tolerance:	20%
Voltage AC:	440 VAC (X1)
Voltage DC:	1000 VDC
Temperature Range:	-40/+110°C
Rated Temperature:	110°C
Dissipation Factor:	1.3% 1kHz
Insulation Resistance:	12 GOhms
Max dV/dt:	2000 V/us
Safety Class:	X1