



Click [here](#) for the 3D model.

| Dimensions | |
|------------|-----------------|
| L | 18.5mm MAX |
| H | 13mm MAX |
| T | 7.3mm MAX |
| S | 15.2mm +/-0.4mm |
| LL | 30mm +5mm |
| F | 0.8mm +/-0.05mm |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 400 |

| General Information | |
|--------------------------|---|
| Series | PMR205/P405 |
| Dielectric | Metallized Paper |
| Style | Radial |
| Features | RC Unit not approved |
| RoHS | Yes |
| Termination | Tinned Wire |
| Lead | Wire Leads |
| AEC-Q200 | No |
| Construction | Molded |
| Typical Component Weight | 2.7 g |
| Miscellaneous | Resistor Tolerance: +/-30%. Resistor= 200 Ohms. |

| Specifications | |
|-----------------------|-----------|
| Capacitance | 0.25 uF |
| Capacitance Tolerance | 20% |
| Voltage DC | 250 VDC |
| Voltage AC | 125 VAC |
| Temperature Range | -40/+85°C |
| Rated Temperature | 85°C |
| Insulation Resistance | 3 GOhms |
| Safety Class | X2 |