



Click [here](#) for the 3D model.

| Dimensions | |
|------------|-----------------|
| L | 30.5mm MAX |
| H | 19mm MAX |
| T | 12.1mm MAX |
| S | 25.4mm +/-0.4mm |
| LL | 6mm -1mm |
| F | 1mm +/-0.05mm |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 800 |

| General Information | |
|--------------------------|---|
| Series | PMZ2035/P435 |
| Dielectric | Metallized Paper |
| Style | Radial |
| Features | RC Unit approved |
| RoHS | Yes |
| Termination | Tinned Wire |
| Lead | Wire Leads |
| Qualifications | ENEC |
| AEC-Q200 | No |
| Construction | Molded |
| Typical Component Weight | 10 g |
| Miscellaneous | Resistor Tolerance: +/-30%. Resistor= 150 Ohms. |

| Specifications | |
|-----------------------|-----------|
| Capacitance | 0.1 uF |
| Capacitance Tolerance | 10% |
| Voltage DC | 1000 VDC |
| Voltage AC | 440 VAC |
| Temperature Range | -40/+85°C |
| Rated Temperature | 85°C |
| Insulation Resistance | 6 GOhms |
| Safety Class | X1 |