



## 18 Watt Universal 3-Wire Input Adapter



### Features

- Low Cost
- Efficiency Level VI Compliant
- Non-vented Case
- Low Profile Design
- Class B EMI

### Applications

- Portable Equipment
- Access Devices
- Peripherals
- Network Hubs

### Safety Approvals

- UL/cUL 60950-1
- CB(IEC60950-1)
- CE

### Mechanical Characteristics

- Length: 103mm (4.06in)
- Width: 49mm (1.93in)
- Height: 33.5mm (1.32in)
- Weight: 140g (4.94oz.)

### Output Specifications

Model	DC Output Voltage	Load		Ripple <sup>(1)</sup> P-P (max.)	Regulation Line & Load
		Min.	Max.		
PSAA18U-120L6	12V	0A	1.5A	120mV	±5%
PSAA18U-150L6	15V	0A	1.2A	150mV	±5%
PSAA18U-240L6	24V	0A	0.75A	240mV	±5%
PSAA18U-480L6	48V	0A	0.38A	480mV	±5%

(1) Measured after 10 minutes warm up at 25°C with 12-inch twisted pair terminated with a 10uF capacitor and 0.1uF ceramic in parallel.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**Input:****AC Input Voltage Rating**

100 to 240V AC

**AC Input Voltage Range**

90 to 264V AC

**AC Input Frequency**

47 to 63Hz

**Input Current**

0.6A (RMS) maximum at 100V AC

0.3A (RMS) maximum at 240V AC

**Leakage Current**

0.25mA maximum at 250V AC and 50Hz

**Inrush Current**

60A for 100V AC at maximum load

150A for 240V AC at maximum load

(Cold start at ambient 25°C)

**Input Power Saving**

&lt;0.075W

**Output:****Efficiency**

DOE Level VI

COC Ver5 Tier 2

**Over-Voltage Protection**

Auto restart

**Over-Current Protection**

Auto restart

**Short-Circuit Protection**

Output can be shorted permanently without damage

**Environmental:****Temperature**

Operation 0 to +40°C

Non-operation -20 to +75°C

Relative Humidity 0 to 90%

**Emissions**

Complies with FCC Class B

Complies with EN55032 Class B

**Immunity**

IEC1000-4-2 Level 4(contact 8kV, air 15kV)

IEC1000-4-3 Level 2

IEC1000-4-4 Level 2

IEC1000-4-5 Level 3

EN61000-4-6 Level 2

EN61000-4-8 Level 1

EN61000-4-11

**Insulation Resistance**

Input to Output : &gt; 10M ohm, 500V DC

Input to Field Ground: &gt; 10M ohm, 500V DC

**Dielectric Withstand (Hi-pot) Test**Primary to Secondary: 3000V AC for 1 min.,  
10mA

Primary to F.G.: 1500V AC for 1 min., 10mA


**Input Connector**

IEC C14

**DC Output Connector**

2.1mm x 5.5mm center positive standard

**Dimension Diagram Unit: mm**



[Type text]