



BURNDY Catalog Number
UPC Number
Description
Status

Q2A312N
 7818103215600
 250-350 CU 2 COND NEMA
 Active

Web Use
 BURNDY Product Line

Dimensional	
Length (in)	4.50
Thickness (in)	5/16
Height (in)	1.69
D or Diameter (Fraction) (in)	3-1/8
Hole Size (Fraction)	9/16
Stud Size (in)	1/2
Thickness	0.31
D - in	3.13
Pad Width (in)	2.38
N (Fraction)	5/8
E - in	1.75
N (in)	0.63
Hole Size (in)	0.56
Length (Fraction)	4-1/2
Height (Fraction) (in)	1-11/16
General	
Number of Holes	2
Product Description	Copper Terminal, 2 Hole, 250-350 kcmil, 1/2" Stud, 1-3/4" Stud Hole Spacing
Conductor(s)	
Copper Solid Size (Range)	N/A
Navy Cable Size (Range)	N/A
Copper Stranded (Range)	250 kcmil-350 kcmil
Physical	
Installation Torque	325
Type of Plating	Unplated
Connector Type	Terminal
Plated (Yes or No)	N
Product Material	Copper
Approvals / Certifications	
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	N
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175