

Eaton molded case circuit breaker accessory shunt trip

HMCP030H1CA12S06

UPC:782114876008

Dimensions:

- **Height:** 6 IN
- **Length:** 3.38 IN
- **Width:** 4.13 IN

Weight:4.5 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Motor circuit protector
- **Amperage Rating:** 30A
- **Number Of Poles:** Three-pole
- **Auxiliary Switch:** 2A-2B right pigtail same side
- **Frame Size:** F-frame
- **Magnetic Trip Range:** 90-300A
- **Maximum Voltage:** 600 Vac, 250 Vdc
- **Series:** Series C
- **Shunt Trip:** 48-127 Vac or 48-60 Vdc left pigtail rear
- **Terminals:** Line and load

Supporting documents:

- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [UL listed 100%-rated molded case circuit breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [Current limiting Series C molded case circuit breakers product aid](#)

- [Power metering and monitoring with Modbus RTU product aid](#)
- [Motor protection circuit breakers product aid](#)
- [Circuit breaker motor operators product aid](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Multi-wire lugs product aid](#)
- [StrandAble terminals product aid](#)
- [Molded case circuit breakers](#)
- [Eaton's Volume 4-Circuit Protection](#)
- [Series C. HMCP Motor Circuit Protectors 3-600 Amperes- Dimension Sheets](#)
- [HMCP and HMCPS Series C F-Frame Motor Circuit Protector - Installation Instructions](#)
- [Breaker service centers](#)
- [Eaton Specification Sheet - HMCP030H1CA12S06](#)
- [Series C F-Frame molded case circuit breakers](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)
- [MOEM MCCB product selection guide](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)

Certifications:

- [UL Listed](#)
- [CSA Certified](#)

Product compliance:

- [Contact Manufacturer](#)