

Eaton molded case circuit breaker accessory trip unit

LT3400KM

UPC:786685376479

Dimensions:

- **Height:** 4.38 IN
- **Length:** 8.5 IN
- **Width:** 4.63 IN

Weight:2.22 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Trip unit
- **Amperage Rating:** 400A
- **Interrupt Rating:** 65 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Trip Type:** Magnetic
- **Used With:** E2LME, E2LMZ series
- **Frame Size:** L-frame
- **Magnetic Trip Range:** 3600-4400A
- **Maximum Voltage:** 600 Vac, 1000Y/577 Vac, 250 Vdc
- **Series:** Series C

Supporting documents:

- [UL listed 100%-rated molded case circuit breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [StrandAble terminals product aid](#)
- [Power metering and monitoring with Modbus](#)

[RTU product aid](#)

- [Current limiting Series C molded case circuit breakers product aid](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Multi-wire lugs product aid](#)
- [Motor protection circuit breakers product aid](#)
- [Circuit breaker motor operators product aid](#)
- [Eatons Volume 4-Circuit Protection](#)
- [Molded case circuit breakers](#)
- [Breaker service centers](#)
- [MOEM MCCB product selection guide](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)
- [Series C F-Frame molded case circuit breakers](#)
- [Eaton Specification Sheet - LT3400KM](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)

Certifications:

- [CSA Certified](#)
- [UL Listed](#)

Product compliance:

- [Contact Manufacturer](#)