



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	200 A
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs

Complementary

Interrupt Rating	22 kA 120/240 V AC 50/60 Hz
Number of Panel Spaces	4
Wire Size	AWG 1...300 kcmil copper or aluminium
Tightening torque	40.71 lbf.in (4.6 N.m)
Height	88.90 mm (3.5 in)
Depth	73.91 mm (2.91 in)
Width	38.10 mm (1.5 in)

Environment

Certifications	UL listed CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	00083-QO BREAKERS 150-200 VH
Discount Schedule	DE2A
GTIN	00785901608929
Package weight(Lbs)	2.64 lb(US) (1.197 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

Contractual warranty

Warranty

18 months
