

QO240PLILC

Mini circuit breaker, QO, 40A, 2 pole, 120/240 VAC, 10 kA, Powerlink, load shedding, plug in mount



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	40 A
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	2P
Ratings	Switching Duty rated
Electrical Connection	Box lugs

Complementary

Interrupt Rating	10 kA 120/240 V AC 50/60 Hz
Number of Panel Spaces	2
Wire Size	AWG 12...AWG 2 aluminium
Tightening torque	40.71 lbf.in (4.6 N.m)
Maximum Height	4.55 in (115.57 mm)
Maximum Depth	2.91 in (73.91 mm)
Maximum Width	1.5 in (38.10 mm)

Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	00026 - QO- PLILC BREAKERS - INTELLIGENT LOAD CENTER
Discount Schedule	DE2A
GTIN	00785901621355
Package weight(Lbs)	0.82 lb(US) (0.37 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------
