



### Main

Range of product	QO
------------------	----

### Complementary

[Ue] rated operational voltage	208Y/120 V AC 240 V AC
AWG gauge	AWG 4...300 kcmil aluminium/copper
Maximum Depth	1.013 in (25.73 mm)
Maximum Height	5.03 in (127.76 mm)
Phase	3 phase
Number of spaces	30
Short-circuit protection	10 kA
Product compatibility	QO circuit-breaker
Product destination	QO circuit breaker QO-GFI circuit breaker QO-EPD circuit breaker
Maximum Width	7.514 in (190.86 mm)
Wiring configuration	3-wire

### Environment

Product certifications	CSA UL
------------------------	-----------

### Ordering and shipping details

Category	00909 - MOUNTING BASES, S/N
Discount Schedule	DE3A
GTIN	00785901868279
Package weight(Lbs)	3.78 lb(US) (1.71 kg)
Returnability	Yes
Country of origin	US

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes

---

RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Circularity Profile	No need of specific recycling operations

---

### Contractual warranty

---

Warranty	18 months
----------	-----------

---