

R30LED-10W-XxW-120AFD (SERIES)

LED Dimmable Light Bulb, R30, E26 Base
120Vac, Angle of illumination: 110°
Halogen White(2700K), Pure White(5000K)



DWG BY:
SWL / GP
10-07-13

R&D:
UF / KS
04-12-18

MFG:
LD
04-12-18

QA:
EE
04-12-18

REVISION LTR: B
ECR#: 041118-GP01
04-11-18

○ **Features**

| | |
|---------------------------|--|
| Operating Temperature | -20°C to +40°C |
| Heatsink Temperature | 50°C |
| Heatsink Material / Color | Aluminum / Silver |
| Housing Material / Color | Polycarbonate / White |
| Lens Material / Color | Frosted White, Polycarbonate, UL94 V-0 |
| ETL / cETL Listed | E4003266 |
| LED LM80 Report | Yes |
| LM79 Report | - |
| Dimmable | Yes |
| Warranty | 3 Years |
| Weight | 0.7 lbs. |



○ **Electro-Optical Characteristics**

| Part Number | R30LED-10W-XHW-120AFD | R30LED-10W-XPW-120AFD |
|-----------------------|-----------------------|-----------------------|
| Input Voltage (typ) | 120Vac | 120Vac |
| Tested @ (Voltage) | 120Vac | 120Vac |
| Power Consumption | 10W | 10W |
| Current Consumption | 0.080 A | 0.085 A |
| Efficacy: (Lm/W) | 90 | 85 |
| Lumens | 880 lm | 850 lm |
| Max Ft-Cd | 265 cd | 275 cd |
| Power Factor | 1.0 | |
| CRI (Ra) | >80 | |
| CCT | 2700K~3000K | 5000K~5600K |
| Color | Halogen White | Pure White |
| Angle of illumination | 110° | |

○ **Dimensions**



TOP VIEW

SIDE VIEW

Notes:

- 1. All Dimensions are in Inches [Millimeters].

Tolerance:

- XXX +/- .010
- XX +/- .025