

R71XI347050H0K

Aliases (71XI347050H0K)

R71H, Film, Metallized Polypropylene, Automotive Grade, 0.47 uF, 10%, 450 VDC, 85°C, 15mm



Click [here](#) for the 3D model.

| Dimensions | |
|------------|------------------|
| L | 18mm +0.3/-0.5mm |
| H | 12mm +0.1/-0.5mm |
| T | 6mm +0.2/-0.5mm |
| S | 15mm +/-0.4mm |
| LL | 25mm +2/-1mm |
| F | 0.8mm +/-0.05mm |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 900 |

| General Information | |
|--------------------------|--|
| Series | R71H |
| Dielectric | Metallized Polypropylene |
| Style | Radial |
| Features | PFC and Pulse |
| RoHS | Yes |
| Termination | Tinned Wire |
| Lead | Wire Leads |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |
| Typical Component Weight | 1.7 g |
| Miscellaneous | Above 105C DC And AC Voltage Derating Is 4%/C. |

| Specifications | |
|-----------------------|---|
| Capacitance | 0.47 uF |
| Capacitance Tolerance | 10% |
| Voltage DC | 450 VDC |
| Voltage AC | 160 VAC |
| Temperature Range | -55/+125°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.1% 25C |
| Insulation Resistance | 63.8298 GOhms |
| Max dV/dt | 100 V/us |
| ESR | 59.26 mOhms (100kHz) |
| Ripple Current | 2.457 Amps (100kHz 85C), 47 Amps (Peak) |
| Inductance | 10 nH |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.