


RDER72J104K8M1C11A

" # " indicates a package specification code.

- Recommended
- Flow OK
- Complies with RoHS
- Anti-noise
- Deflecting crack
- Soldering crack

< List of part numbers with package codes >
RDER72J104K8M1C11A

Shape



L size or outer diameter D (mm)	7.5 mm max.
W size	5.5 mm max.
T size	3.15 mm max.
Lead spacing F	5 +0.6/-0.2mm
Lead diameter d	0.5 ± 0.05mm
W1 size (max.)	8.0mm

References

Packaging	Specifications	Minimum quantity
	Ammo pack taping type	1500

Specifications

Capacitance	0.10μF ± 10%
Rated voltage	630Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

⚠ Attention

- This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.